

P.M 34

32273-9

4/17/98

page 184

BEGIN FRONT PANEL

BEHR (logo)

NO. 90

EXTERIOR • GREEN • WATER REPELLENT

**DOCK & FENCE POST
PRESERVATIVE**

**FOR WOOD IN CONTACT WITH SOIL & WATER
PROTECTS AGAINST WOOD ROT, WARPING, SWELLING
TERMITE DAMAGE, MILDEW AND MOISTURE**

(pictures of dock and fencepost)

FOR WOOD ABOVE OR BELOW GROUND
IN CONTACT WITH SOIL OR WATER

**KEEP OUT OF REACH OF CHILDREN
WARNING! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL
OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.**

See Back Panel for Precautionary Statements and First Aid.

EPA Reg. No. 32273-9
EPA Est. No. 32273-CA-1

ACTIVE INGREDIENT:

*Copper Naphthenate

INERT INGREDIENTS:

TOTAL

25.0%
75.0%
100.0%

(* 2.50% copper as metallic)


Contains: Petroleum Distillates & Copper Naphthenate

ONE U.S. GALLON - 3.9L

V.O.C. LESS THAN 550 Grams/Liter

4.6 Lbs./Gal. V.O.S.

LIMITED WARRANTY: Since BEHR PROCESS CORPORATION has no control over proper surface preparation or application methods, no guarantee as to the results is offered, expressed or implied. BEHR guarantees the contents of the can only. If the product is defective, replacement material will be furnished free of charge or a refund of the material cost at manufacturer's



option. Labor costs are not covered by the warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the material.

END FRONT PANEL

BEGIN BACK PANEL

IMPORTANT: DO NOT OPEN CAN WITHOUT READING ALL INSTRUCTIONS.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING! HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. CAUSES SKIN IRRITATION. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid breathing vapor or spray mist during brush, roll, spray or dip applications. Wear a NIOSH/MSHA approved mist/vapor respirator when spraying for continued or prolonged use of this product or the frequent use of this product. Use in a well ventilated area.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters or rinsate.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE LIQUID AND VAPOR. Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after each use.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.
IF SWALLOWED: Drink promptly large quantities of milk, egg white, and gelatin mixture, or, if these are not available, large quantities of water. Avoid alcohol. Do not induce vomiting as it may cause respiratory pneumonia. **CALL PHYSICIAN IMMEDIATELY.**
IF IN EYES: Flush with plenty of water and get immediate medical attention.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal.
STORAGE: Do not store unused product inside the home. Store at temperatures between 40° F and 100° F. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbant, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Keep container closed when not in use.
DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **For Exterior Use Only.** Application of this product may produce a strong, lingering, unpleasant odor.

BEHR NO. 90 TERMITE & ROT-STOPPING WOOD PRESERVATIVE is a ready-to-use, water repellent, wood preservative specifically designed for exterior, above or below ground, wood in contact with soil, concrete or water. This copper naphthenate wood preservative and insecticide provides protection against moisture, rot, mildew and termite damage. Although this product contains copper fungicide which provides a green cast, it is not intended for use as a stain.

WHERE TO USE:

- Below ground or near water, exterior new or old unfinished wood, including pressure-treated, such as foundations, sills, docks, boats, and fence posts.
- Do not apply to food or feed contact surfaces. Do not contaminate drinking water with treated wood.
- For wood that is above ground and not near water, use BEHR NO. 89 CLEAR WOOD PRESERVATIVE.

PREPARATION:

- Wood should be clean, dry, well seasoned and free of bark, paint, varnish, wax or other films.
- All unsound wood should be removed at least 2 feet beyond any evidence of decay to control insects.

APPLICATION AND COVERAGE:

- Use at package consistency. **DO NOT THIN.**
- Treated wood should be at least two feet away from edible plants, vegetables and fruit trees due to the formula containing copper naphthenate.
- Apply liberally by brushing, rolling, spraying or dipping.
- To dip wood, soak 3 to 30 minutes per inch of thickness. Fence posts, poles, foundations, timbers, and heavy wooden parts should be immersed in the product for 12 to 48 hours.
- Apply at a spread rate of approximately 100-300 sq. ft. per gallon, depending on porosity and method of application.
- Apply two liberal coats immediately following each other.
- Thoroughly saturate edge and end grain, including saw cuts. The more preservative absorbed by the wood, the longer and more effective the protection.

DRY TIME:

- Allow **BEHR TERMITE & ROT-STOPPING WOOD PRESERVATIVE** 12-16 hours, longer if exposed to high humidity and/or low temperatures

CLEAN-UP:

- Clean all tools with paint thinner or mineral spirits.
- Remove drips and spatters while product is still wet. If dried, use paint remover.

In case of medical questions, emergencies or accidents involving this product, call Chem-Trec at 1(800) 424-9300.

BEHR PROCESS CORPORATION, SANTA ANA, CA 92704

4 8 4

END BACK PANEL

)

