



JAN 2 1976
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act



WOOD PRESERVATIVE

**CLEAR, PAINTABLE, WATER REPELLENT.
STOPS WARPING, ROT, TERMITES**

NET 32 FL. OZ. (1 QT.)

WARNING:
KEEP OUT OF
REACH OF
CHILDREN
See additional
precautions on side
panel.

Active Ingredients:	4.2%
Pentachlorophenol	
Other Chlorophenols & Related Compounds	.8%
Inert Ingredients	95.0%
Total	100.0%

**WARNING: COMBUSTIBLE MIXTURE
HARMFUL OR FATAL IF SWALLOWED OR
ABSORBED THROUGH SKIN. CAUSES SKIN
IRRITATION. MAY PRODUCE DELAYED
CHEMICAL BURNS. CONTAINS PETROLEUM
DISTILLATES.**

**DO NOT USE, POUR, SPILL OR STORE NEAR
HEAT OR OPEN FLAME.**

Do not breathe spray mist. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors or any other confined areas where the vapors may concentrate and cause injury to plant or animal life.

FIRST AID:
External: For skin contact, wash with soap and water. For eye contact, flush with water and get medical attention.
Internal: If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY**

ENVIRONMENTAL CAUTION:
This product is toxic to fish and wildlife. Keep out of lakes, streams and ponds. Keep containers closed when not in use. Do not contaminate water by cleaning off equipment or disposal of wastes. Apply this product only as specified on this label.

NOTICE: Do not reuse empty container. Destroy, bury in a safe place or burn. If burned, stay away from smoke and fumes.

WOOD PRESERVATIVE

**CLEAR, PAINTABLE, WATER REPELLENT.
STOPS WARPING, ROT, TERMITES**

Duro Wood Preservative is not a surface coating. It penetrates below the surface carrying solids into pores. This action plugs up the pores and as a result does the following:

A - Prevents absorption and retention of moisture which causes warping, twisting, shrinking, and rotting.

B - Becomes an effective water proof and mold resisting overcoat.

C - Seals and restores life to old, unglued, warped and damaged wood (helps them lie flat again, solid in frame, etc.) Also seals exterior particle board and other lumber products.

This product is effective for application to wood, plywood, fiberboard, Plywood Post (Lytus), Beams and Columns. It is not effective on concrete. Therefore, thoroughness of treatment is essential for proper results.

DIRECTIONS:
Wood must be clean, dry and free from paint, oil, varnish. Do not use steel wool before applying.

Recommended application is by total immersion in 40°F. water for 24 hours. Suitable immers. in 100°F. water enough to penetrate wood. See technical chart for suggested immersion periods.

Malware and other items to be preserved should be immersed in water for 24 hours. Plywood and veneer should be immersed in water for 24 hours. Structural lumber should be immersed in water for 24 hours.

Wood to be in contact with water for 24 hours. Well seasoned, peeled and kiln dried wood should be immersed in water for 24 hours.

Hammers and impact tools should not be used on treated wood. A brush can be used. Apply generously to surfaces and allow to dry thoroughly. Apply to all surfaces. Do not use on painted surfaces. Successive coats must be applied before final drying.

Coverage:
Brush - Average 150 sq. ft. per gallon.
Immersion - Average 100 sq. ft. per gallon.
3 min. 5.16 gal./30 min. 10.15 gal./24 hr. 15.21 gal.

**EPA. REG. NO. 32447-1
EPA. EST. 35893-OH-1**

DURO WOODHILL CHEMICAL SALES CORPORATION
a member of the **BOCTITE** group of companies