



ecolochem

WATER TREATMENT SINCE 1954

DCA-10

COMPOSITION

	<u>PERCENT BY WEIGHT</u>
Active ingredient	20.0 percent
Poly (oxyethylene (dimethyliminio) ethylene (dimethyliminio)-ethylene dichloride)	20.0 percent
Inert ingredient	80.0 percent
Weight per gallon	8.69 pounds
Weight of active ingredient per gallon	1.74 pound

APPLICATION

DCA-10 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 2.9 to 7.3 fluid ounces of DCA-10 per 1000 gallons of water to provide a concentration of 24 to 60 parts per million of DCA-10 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.73 to 7.3 fluid ounces of DCA-10 per 1000 gallons of water (5 to 60 parts per million of DCA-10) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse containers. Destroy when empty.

1067 CASCADE BLVD.
 CASCADEVILLE, VT. 28324
 (603) 543-4775

MADE IN U.S.A.

DCA-10 - EPA-REG. NO. 32972-2

1245 BURLINGTON ST.
 OPA-DOCK, FLA. 32054
 (305) 444-1111

ACCEPTED
March 18, 1974
 32972-2

32972-2