

GIL-CIDE

1201

Manufactured by: Gilbert Chemical Company
Belleville Industrial Park
Belleville, New Jersey 07109
EPA REG. NO. 33133-1

NET WEIGHT:

ACCEPTED
33133-1
MAY 2 1980

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
UNDER NO.

ACTIVE INGREDIENT

Poly(oxyethylene (dimethyliminio) ethylene-
(dimethyliminio) ethylene dichloride) 30.0%

INERT INGREDIENT 70.0%

This product contains 2.67 lb. of active ingredient per gallon and weighs
8.90 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact
with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg
whites, gelatin solution, or if these are not available drink large quantities of
water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of
lake, streams, or ponds. Permits may be required for discharges containing
this pesticide into lakes, streams, ponds or public water. For guidance,
contact the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner
inconsistent with its labeling.

GIL-CIDE 1201 is used to control algae, bacteria, and fungi in
recirculating commercial and industrial water cooling towers. Prior to its
use, systems must be cleaned to remove algal growth, microbiological
slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces
of GIL-CIDE 1201 per 1000 gallons of water to provide a concentration of
16 to 40 parts per million of GIL-CIDE 1201, based on the total weight of
water in the system, is recommended. Repeat initial dosage until control is
evident.

Subsequent slug additions of 0.47 to 4.75 fluid ounces of GIL-CIDE 1201
per gallons of water (4 to 40 parts per million of GIL-CIDE 1201) should
be employed every 2 to 5 days, or as needed. The frequency of addition
depends upon the relative amount of bleedoff and the severity of the micro-
biological problem. Slug additions should be made in the sump of water
cooling towers.

GIL-CIDE 1201 is used to control bacteria in industrial air-washing
systems that maintain effective mist eliminating components. Prior to its
use, systems should be cleaned to remove bacterial slime and other
deposits. An initial slug dose of 7.1 to 11.9 fluid ounces of GIL-CIDE 1201
per 1000 gallons of water is recommended. Repeat initial dosage until
control is evident. Subsequent slug additions of 4.8 to 11.9 fluid ounces of
GIL-CIDE 1201 per 1000 gallons of water should be employed each 1 to 5
days, or as needed. The frequency of addition depends upon the relative
amount of bleedoff and severity of the bacterial problem. Slug additions
may be made to the sump or to the water collection trays of the airwash
system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not
contaminate water, food, or feed by storage, disposal, or cleaning of
equipment. The container must be triple rinsed (or equivalent) and offered
for recycling, reconditioning, or disposal in an approved landfill or buried in
a safe place. Rinsate that cannot be used or reprocessed should be
disposed of in a landfill approved for pesticides or buried in a safe place
away from water supplies. Open dumping is prohibited.

Manufactured by:
Gilbert Chemical Company
Belleville Industrial Park
Belleville, N.J. 07109

EPA REG. NO. 33133-1

EPA EST. NO. 33133-NJ-18