

# SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE

Twin-Chain Quaternary  
Ammonium Compound Concentrate  
Water Treatment Microbiocide  
for Building and Industrial  
Cooling Towers and Oil Field Water  
Flood or Salt Water Disposal Systems

### Active Ingredients

Didecyl dimethyl ammonium chloride

### Inert Ingredients

ACCEPTED  
AUG 15 1980  
EPA Reg. No. 33355-6

**KEEP OUT OF REACH OF CHILDREN.**

**DANGER**

### Statement of Practical Treatment

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution; or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

SEE LEFT PANEL FOR  
ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Registration No. 33355-6  
EPA Establishment No. 33355-NC 01  
Net Weight 445 lbs.  
Net Volume 55 gals.

SOUTHEASTERN LABORATORIES  
P. O. Box 1138 Goldsboro, N. C.  
919-735-9222

### Directions for use GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. To control algae and bacterial slimes, use SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE as directed. For best results, slug feed. The frequency of addition of microbiocide needed depends on many factors. To optimize your use of SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE, follow this procedure.

**Recirculating Cooling Towers**  
Initially, use 20 fluid ounces per 1000 gallons of water to be treated (20 ppm active quaternary). Should the above dosage not give satisfactory results, use 30 fluid ounces per 1000 gallons of water.

Repeat the initial dose every seven days or increase the frequency if needed.  
2 When the above treatment level is successful, use 6.7 to 10 fluid ounces per 1000 gallons of water to maximize efficiency. Repeat weekly as needed.  
Should slime develop again, go back to initial dosage.

Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages. Slug feed every seven days.

Drate the appropriate amount of SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE in 1 or 2 gallons of water, then add to the tower. Note this product weighs 8.09 lbs. per gallon (at 20°C).

Should tower be heavily fouled, a precleaning is required.

**Oil Field Water Flood or Salt Water Disposal Systems** Do not apply in Marine and Estuarine Oil Fields.

1 For the control of slime forming and sulfate reducing bacteria in oilfield water flood or salt water disposal systems, add 5-10 ppm (active) SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE (5 - 10 gallons per 3000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.

2 For intermittent use, dose at a rate of 5-20 ppm (active) SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE (5 - 20 gallons per 3000 barrels of water) for 48 hours per day, one to four times a week as needed to maintain control.

And SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE directly from the drum with the proper type of metering equipment. This product weighs 8.09 lbs. per gallon (at 20°C).

28

SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE will control algae and bacterial slimes found in recirculating cooling tower waters and oil field water flood. SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE helps clean and loosen slime debris from cooling and flooding system surfaces. When used in slug doses, no other microbiocide is required.

SOUTHEASTERN LABORATORIES H-9 MICROBIOCIDE is economical to use because it is concentrated. It should be handled with care.

### Precautionary Statements

#### Hazards to

#### Humans and Domestic Animals

### DANGER

Keep Out of Reach of Children. Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge treated effluent into lakes, streams, ponds or public waters unless in accordance with a NPDES permit. For guidance contact your Regional Office of the Environmental Protection Agency.

### STORAGE AND DISPOSAL

#### PROHIBITIONS

DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL.

OPEN DUMPING IS PROHIBITED

DO NOT REUSE EMPTY CONTAINER

#### PESTICIDE DISPOSAL

PESTICIDE THAT CANNOT BE USED, OR CHEMICALLY REPROCESSED SHOULD BE DISPOSED OF IN A LANDFILL APPROVED FOR PESTICIDES OR BURIED IN A SAFE PLACE AWAY FROM WATER SUPPLIES

#### CONTAINER DISPOSAL

DISPOSE OF IN AN INCINERATOR OR LANDFILL APPROVED FOR PESTICIDE CONTAINERS. BURY IN A SAFE PLACE OR RETURN TO DRUM RECONDITIONER

#### GENERAL

CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES