

BEST DOCUMENT AVAILABLE

# SELCide™ 511

### ACTIVE INGREDIENTS

Potassium dimethyldithiocarbamate . . . . . 10.0%  
INERT INGREDIENTS . . . . . 90.0%

This product contains 0.87 lb. of active ingredient per gallon and weighs 9.68 lb. per gallon.

## KEEP OUT OF REACH OF CHILDREN WARNING

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING:** Causes eye damage and skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

**STATEMENT OF PRACTICAL TREATMENT:** In case of skin contact, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, call a physician immediately. If patient is conscious, induce vomiting by stroking or tickling the patient's throat or the back of patient's tongue. Emetics such as 2 teaspoonfuls (10 mL) of special syrup or 1 teaspoonful (5 mL) of dry mustard in warm water to form a paste, or even soap in warm water can be used. Repeat until vomit fluid is clear. Then have patient drink plenty of milk, gelatin solution, water, egg whites, flour and water, or other non-oily diluent. Fever or face swelling or general itching by mouth to an allergic patient.

**Note to physician:** Probable mucosal damage may contraindicate gastric lavage.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Do not discharge treated effluent into lakes, streams, ponds, or public waters unless in accordance with a NPDES permit. For guidance, contact your Regional Office of the Environmental Protection Agency.

### DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SELCide™511 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of SELCide™511 in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 12.0 to 17.9 fl. oz. of SELCide™511 per 1000 gal. of water to provide 100 to 150 ppm of SELCide™511, based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 6.0 to 17.9 fl. oz. of SELCide™511 per 1000 gal. of water (50 to 150 ppm SELCide™511) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

SELCide™511 is used in industrial air washing systems which maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 28.1 to 35.9 fl. oz. of SELCide™511 per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 21.0 to 35.9 fl. oz. of SELCide™511 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system.

### STORAGE AND DISPOSAL

**PROHIBITIONS:** Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide spray mixture, or rinseate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides, or buried in a safe place away from water supplies.

#### CONTAINER DISPOSAL:

**METAL:** Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place. Containers over 30 gallons should be resealed before offering for reconditioning.

**PLASTIC:** Containers under 30 gallons must be not reused but should be triple rinsed and disposed of in a incinerator or landfill approved for pesticide containers or buried in a safe place. Containers over 30 gallons are to be resealed and offered for reconditioning or triple rinsed (or equivalent) and offered for recycling, reconditioning or disposal in an approved landfill or buried in a safe place.

**GENERAL:** Consult Federal, State, or Local disposal authorities for approved alternative procedures.



Manufactured by:  
Southeastern Laboratories, Inc.  
P. O. Box 1138  
Goldshoro, N. C. 27530 0024

EPA Reg. No. 23355-9

EPA Est. No. 33355-NC-01

Net Contents

33355-9