

SERVICE

# STAA-CLEAR WR 1-5

QUALITY

## WATER REPELLENT WOOD PRESERVATIVE

### INGREDIENTS

#### ACTIVE INGREDIENTS:

Pentachlorophenol .....	21.70%
Other Chlorinated Phenols .....	2.53%
Petroleum Hydrocarbons .....	30.70%

**INERT INGREDIENTS** .....

45.01%

100.00%

\*Equivalent to 25.3% Technical Pentachlorophenol as defined by Federal Specification TT-W-570.

### RECOMMENDED USE

Recommended for use on arbors, cabinets, fence posts, fence rails, floors, furniture, doors, porsts, porches, shingles, steps, storm sashes, screens, sills, stairs, sub-flooring and wall paneling. Protects wood against warping, checking, shrinking, swelling, termites, powder post beetles, rot, stain, decay, and end-checking caused by changes in moisture content.

Powder post beetles which invade furniture, flooring and structural lumber are killed by application of **STAA-CLEAR WR 1-5**. They will not attack wood treated with **STAA-CLEAR WR 1-5**.

### NON-WARRANTY

Neither Revico nor seller makes any representation or warranty, express or implied, concerning this material, except that it meets ingredient statement. Buyer assumes all risk of use and handling when such use and handling is not in accordance with label instructions.

This product is toxic to fish. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

Do not reuse containers! Destroy when empty!

DO NOT USE, LEAK, SPILL OR STORE NEAR HEAT OR OPEN FLAME!

EPA Reg. No. 11190-7

### DIRECTIONS FOR USE

Mix by diluting one volume of **STAA-CLEAR WR 1-5** Concentrate with 1-2 volumes of mineral spirits or other suitable solvent and agitate well. Allow **STAA-CLEAR WR 1-5** container to warm prior to mixing so that viscosity will be lowered to permit good mixing. Store indoors in winter or in cold storage.

Best results will be obtained if wood to be treated is immersed in ready-to-use solution for 3 minutes or longer. Apply at least 2 liberal brush or spray applications if dipping is not possible. Make certain all areas are fully treated to get maximum results. Allow at least one hour between applications and at least 24 hours for drying before painting or varnishing. When drying conditions are poor, where longer soaking periods are used, or where wood is unusually absorptive, drying time before painting should have to be increased. Fence posts, poles, foundation timbers and heavy wood members should be free of bark, dry and well-seasoned and immersed in the diluted product for a period of 12 to 48 hours to be an effective wood preservative. In areas where dry wood termites are present all interior trim, as well as all exterior trim, should be dipped for 3 minutes in ready-to-use **STAA-CLEAR WR 1-5** solution. Keep dip tanks free from water since water will be taken out of water and **STAA-CLEAR WR 1-5** will flake on the solution.

### WARNING KEEP OUT OF REACH OF CHILDREN!

- Harmful if swallowed!
- Harmful if absorbed through skin!
- Do not breathe spray or vapor!
- Do not get in eyes or on clothing!
- Wash thoroughly after handling!
- Avoid contamination of feed or food stuff!
- Wear rubber gloves when handling freshly treated lumber!

33-160-5

ACCEPTED  
7/12/70

1596

ACT  
SUBJECT  
PANTS

# REVICO, INC. MEMPHIS, TENNESSEE

**SERVICE**

# STAA-CLEAR WR 1-5

**QUALITY**

## WATER REPELLENT WOOD PRESERVATIVE

### INGREDIENTS

#### ACTIVE INGREDIENTS:

Pentachlorophenol	21.76%
Other Chlorinated Phenols	2.53%
Petroleum Hydrocarbons	30.70%

**INERT INGREDIENTS** ..... 45.01%

100.00%

\*Equivalent to 25.3% Technical Pentachlorophenol as defined by Federal Specification TT-W-570.

### RECOMMENDED USE

Recommended for use on arbor, cabinets, fence posts, fence rails, floors, furniture, doors, joists, porches, shingles, steps, storm sashes, screens, sills, stairs, sub-flooring and wall paneling. Protects wood against warping, checking, shrinking, swelling, termites, powder post beetles, rot, stain, decay, and mold checking caused by changes in moisture content.

powder post beetles which invade furniture, flooring and structural lumber are killed by application of **STAA-CLEAR WR 1-5**. They will not attack wood treated with **STAA-CLEAR WR 1-5**.

### NON-WARRANTY

Neither Revico nor seller makes any representation or warranty, express or implied, concerning this material, except that it meets ingredient statement. Buyer assumes all risk of use and handling when such use and handling is not in accordance with label instructions.

This product is toxic to fish. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

Do not reuse containers! Destroy when empty!

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME!

EPA Reg. No. 11590-7

### DIRECTIONS FOR USE

Mix by diluting one volume of **STAA-CLEAR WR 1-5** Concentrate with two volumes of mineral spirits or other suitable solvent and agitate well. Allow **STAA-CLEAR WR 1-5** container to warm prior to mixing so that viscosity will be lowered to permit good mixing. Store indoors in winter or in cold period.

Best results will be obtained if wood to be treated is immersed in ready to use solution for 3 minutes or longer. Apply at least 2 liters per brush or spray application if dipping is not possible. Make certain all areas are fully treated to get maximum results. Allow at least one hour between applications and at least 24 hours for drying before painting or varnishing. When drying conditions are poor, where longer soaking periods are used, or where wood is unusually absorptive, drying time before painting would have to be increased. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well seasoned and immersed in the diluted product for a period of 12 to 48 hours to be an effective wood preservative. In areas where dry wood termites are present, all interior trim as well as all floor joists should be dipped for 3 minutes in ready to use **STAA-CLEAR WR 1-5** solution. Keep dip tanks free from water since even the presence of water and **STAA-CLEAR WR 1-5** will darken the solution.

### WARNING KEEP OUT OF REACH OF CHILDREN!

Harmful if swallowed!  
Harmful if absorbed through skin!  
Do not breathe spray or vapor!  
Do not get in eyes or on clothing!  
Wash thoroughly after handling!  
Avoid contamination of food or food stuffs!  
Wear rubber gloves when handling freshly treated lumber!

335605

ACCEPTED

7/11/72

1596

AGS

# REVICO, INC. MEMPHIS, TENNESSEE