To be used only for inhibition and prevention of Algae in Evaporative Condensers and Recirculating Water Cooling Towers as recommended by OLIN SERVICE ENGINEER.



## COMPLETE WATER TREATING CHEMICALS

# MEMPO® ALGICIDE #1

## FOR PROPER TREATMENT OF GOODING WATER

to prevent & control ALGAE

MEMPO ALGICIDE No. 1 is recommended for evaporative condensers and open recirculating water cooling towers.

MEMPO ALGICIDE No. 1 can be prescribed to meet virtually any cooling system problem that involves algae c odors.

Each formulation of MEMPO ALGICIDES contains different primary: we gredients toxic to the Algae growth. Thus two different formulations should be kept on hand to be alternated at regular intervals.

#### DIRECTIONS FOR USE

For best results slug feed, beginning treatment before system has become fouled with algae, or after cleaning system whose efficiency has been reduced by such fouling. Badly fouled systems must be cleaned before treatment is begun.

INITIAL DOSAGE: When system is noticeably fouled, add 0.8 pounds Mempo Algicide No. 1 for each 1,000 gallons of water in the system. Apply at a point where the product will be uniformly mixed with water. Repeat until control is achieved.

SUBSEQUENT DOSAGE: When algae control is evident, add 0.4 - 0.8 lbs. of Mempo Algicide No. 1 for each 1,000 gallons of water in the system every week or as needed to maintain control.

Active Ingredients: Sulfonated Cresol

### WARNING

#### Keep Out Of Reach Of Children

Avoid contact with eyes, kin or clothing. In case of contact, wash skin with planty of water. Flush eyes for at least fifteen minutes and get medical attention. AVOID breathing dust. May be fatal if swallowed or absorbed through the skin.

#### ANTIDOTE

In case of swallowing, give a tablespoon of salt in glass of warm water. Repeat until vomit is clear Call a physician.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contamina e water by cleaning of equipment or disposal of waste. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

EPA Registration No. 1258-954-AA-50607

8 73

11.1%

5.6%

83.3%



KANSAS CITY, KS 66115

NEW YORK, NY 10027

LOS ANGELES, CA 90058

OLIN CHEMICALS, OLIN CORPORATION, STAMFORD, CT 06904