

OLIN 3302

EPA Est. No.
33576-CA-1
33576-KS-1
33576-NY-1

bactericide and fungicide for use in industrial recirculating cooling water systems and cane sugar mills

DIRECTIONS FOR USE:

OLIN 3302 is highly effective for controlling the growth of bacteria and fungi in industrial recirculating water cooling towers, evaporative condensers, air washers, and cane sugar mills.

INDUSTRIAL CIRCULATING COOLING WATER SYSTEMS: Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Badly fouled systems must be cleaned before treatment is begun. For best results slug feed at a point in the system where the product will be well mixed.

INITIAL DOSE: Apply 13.06 fl. oz. Olin 3302 per 1,000 gal. water in system (120 ppm). Repeat weekly or more frequently, if needed to control growth of slime-forming organisms.

SUBSEQUENT DOSE: When control is evident, add 15 to 4.36 fl. oz. Olin 3302 per 1,000 gal. water in system (20-40 ppm) every three days, if needed.

CANE SUGAR MILLS: See Product Bulletin for Olin 3302 Cane Sugar Mill Bactericide-Fungicide for use directions.

ACTIVE INGREDIENTS

Sodium Dimethyldithiocarbamate 15%
Nabam (Disodium Ethylene Bisdithiocarbamate) 15%

INERT INGREDIENTS

70%

EPA Reg. No. 33576-36-AA-50607

WARNING

Keep Out Of Reach of Children

Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reusing.

If swallowed, drink promptly a large quantity of milk or water, or gelatin solution or if these are not available, drink water continuously of water. Call a physician immediately.

This product is toxic to fish. The treated effluent should not be discharged where it will drain into lakes, streams, ponds or other water bodies. To minimize water pollution by cleaning, for equipment, use a lot of water.

Do not reuse empty containers. Containers should be triple rinsed before crushing. Discard containers in a safe place.

FOR INDUSTRIAL USE ONLY

Repackaged By

Gal. Net Contents