



OCT 15 1982

EPA Reg. No.
33576-39

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 33576-39

OLIN 3306

For use in recirculating cooling water towers and air washer systems to control

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CORROSIVE - CAUSES EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling. **ENVIRONMENTAL HAZARDS** - This pesticide is toxic to fish and wild life. Do not discharge into lakes, streams, ponds, or public water unless in accordance with an NPDES permit. For guidance, contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. If plastic, do not reuse empty container.

DISPOSAL: Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of in a land fill approved for pesticides or buried in a safe place away from water supplies. Triple rinse (or equivalent) ALL containers and, for metal containers offer for recycling or reconditioning (for plastic containers dispose in a land fill approved for pesticides). Consult federal, state or local disposal authorities for approved alternative procedures.

ACTIVE INGREDIENTS

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%

INERT INGREDIENTS	98.50%
TOTAL	100.00%

OLIN 3306 weighs 8.4 lbs. per gallon

Keep Out Of Reach Of Children

DANGER

FIRST AID - STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

It is a violation
with its label
Badly fouled

INDU

For the control
distribution by
INITIAL DOSE
OLIN 3306 (1)
1000 gallons of
SUBSEQUENT
OLIN 3306 (1)
gallons of water

NOTE: For use
mist eliminating
Add to air wash
ppm Olin 3306
per 1000 gallons
elimination for
air washer sys
INITIAL DOSE
Olin 3306 (1)
gallons of water
SUBSEQUENT
Olin 3306 (1)
gallons of water

882

FOR INDUSTRIAL USE ONLY

Olin WATER SERVICES Overland Park, Kansas 6
Olin Corporation Stamford, Conn. 06904

BEST DOCUMENT AVAILABLE



OCT 15 1982

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 5552-59

OLIN 3306

EPA Est. No.
33576-KS-1

For treating cooling water towers and air washer systems to control algae, bacteria and fungi

STATEMENTS
DOMESTIC ANIMALS
NO SKIN BURNS. MAY CAUSE
ILLNESS IF INHALED. MAY BE FATAL IF

Wear goggles or face shield and
avoid vapor or mist. Avoid con-
tact with food. Wash thoroughly after handling.
This is toxic to fish and wild life.
Do not use in public water unless in ac-
cordance with local health department.
For cleaning of equipment or disposal
follow directions on this label.

DISPOSAL
Do not feed by storage or disposal.
Do not reuse empty container.
Do not use or chemically reprocessed
for pesticides or buried in a safe
for equivalent. ALL containers
must be decontaminated (for plastic
in land fill approved for pesti-
cide federal, state or local disposal
laws).

ACTIVE INGREDIENTS	
5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS	
TOTAL	98.50%
	100.00%

OLIN 3306 weighs 8.4 lbs. per gallon

Keep Out Of Reach Of Children

DANGER

FIRST AID - STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Badly fouled systems must be cleaned before treatment is begun.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi, add Olin 3306 to the tower basin, distribution box or some other point to ensure uniform mixing.

INITIAL DOSE - When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE - When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

NOTE: For use only in industrial air washing systems that maintain effective mist eliminating components.

Add to air washer sump or chill water sump to insure uniform mixing. 35 to 883 ppm Olin 3306 (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

INITIAL DOSE - When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE - When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water) weekly or as needed to maintain control.

FOR INDUSTRIAL USE ONLY

Gal. Net Contents

Olin WATER SERVICES Overland Park, Kansas 66210
Olin Corporation Stamford, Conn. 06904

BEST DOCUMENT AVAILABLE