

BEST AVAILABLE COPY

ACCEPTED

APR 26 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 33576-39



EPA Reg. No.
33576-39

OLIN 3306

EPA Est. No.
33576-KS-1

For use in recirculating cooling water towers and air washer systems to control algae, bacteria and fungi

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CORROSIVE CAUSES EYE DAMAGE AND SKIN BURNS MAY CAUSE ALLERGIC SKIN REACTION MAY BE HARMFUL IF INHALED MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Apply to pesticide only as specified on this label.

OLIN 3306 weighs 8.4 lbs per gallon

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID - STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Possible mucous damage may contraindicate the use of gastric lavage. Measure against circulatory shock, respiratory depression and convulsions may be needed.

ACTIVE INGREDIENTS

5-Chloro-2-methyl-4-isothiazolin-3-one
2-Methyl-4-isothiazolin-3-one

1.15%

0.35%

INERT INGREDIENTS

98.50%

TOTAL

100.00%

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Keep container closed when not in use. Don't drop, roll or skid drum. Store in a dry location away from excessive heat. Do not reuse empty container.

DISPOSAL:

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Badly fouled systems must be cleaned before treatment is begun.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi, add Olin 3306 to the tower basin, distribution box or some other point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

NOTE: For use only in industrial air washing systems that maintain effective mist eliminating components.

Add to air washer pump or chill water pump to insure uniform mixing. 35 to 883 ppm Olin 3306 (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system) depending upon the severity of contamination in control bacteria, fungi and algae which cause fouling in industrial air washer systems.

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water) weekly or as needed to maintain control.

FOR INDUSTRIAL USE ONLY

Gal. Net Contents

Olin WATER SERVICES
Olin Corporation

Overland Park, Kansas 66210
Stamford, Conn. 06904

EPA Reg. No.
33576-39

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under
EPA Reg. No. 33576-39

BEST AVAILABLE COPY

WATER SERVICES

OLIN 3306

EPA Est. No.
33576-KS-1

For use in recirculating cooling water towers and air washer systems to control algae, bacteria and fungi

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CORROSIVE - CAUSES EYE DAMAGE AND SKIN BURNS MAY CAUSE ALLERGIC SKIN REACTION MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS - This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Apply this pesticide only as specified on this label.

OLIN 3306 weighs 8.4 lbs. per gallon

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID - STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

ACTIVE INGREDIENTS	
5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS	
	98.50%
TOTAL	100.00%

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Keep container closed when not in use. Don't drop, or skid drum. Store in a dry location away from excessive heat. Do not reuse empty container.

DISPOSAL:

Container Disposal: Triple rinse for equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

Pesticide Disposal: "Pesticide wastes" are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Badly fouled systems must be cleaned before treatment is begun.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi, add Olin 3306 to the tower basin, distribution box or some other point to ensure uniform mixing.

INITIAL DOSE - When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE - When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

NOTE: For use only in industrial air washing systems that maintain effective mist eliminating components.

Add to air washer sump or chill water sump to insure uniform mixing. 35 to 883 ppm Olin 3306 (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

INITIAL DOSE - When the system is noticeably fouled, apply 148 to 883 ppm Olin 3306 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Olin 3306 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE - When microbial control is evident, add 35 to 219 ppm Olin 3306 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Olin 3306 per 1000 gallons of water) weekly or as needed to maintain control.

1084

FOR INDUSTRIAL USE ONLY

Gal. Net Contents

Olin WATER SERVICES
Olin Corporation

Overland Park, Kansas 66210
Stamford, Conn. 06904