UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JAN 0 6 1999

Albright & Wilson UK Limited 210-222 Hagley Road West Oldbury, Warley West Midlands, United Kingdom B68 ONN

Subject: Tolcide PS352C

EPA Registration No. 33677-5 Notification Per PR-Notice 95-2

Your Notification Dated December 9, 1998

Dear Mr. Harrison:

This will acknowledge receipt of your notification to revise your label submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,

Marshall Swindell

Notification Coordinator

Regulatory Management Branch I Antimicrobials Division (7510C)

GONCURRENCES									
5710C									
RUPULANE) P. K. FOST]		,				******		
1/4/39									

PM	33
FILL	رزب

33617-5

2 of 4

· · · · · · · · · · · · · · · · · · ·		red, OMB No. 2070-0060, Approval expires 05-31-			
EPA Emuinos	United States	Registration	OPP Identifier Number		
Environ	mental Protection Agen	cy	251534		
	Washington, DC 20460	to Other			
	Application	on for Pesticide - Section 1	j		
1. Company/Product Number		2. EPA Product Manager	3. Proposed Classification		
33677-5					
A. Company (Duration of Ottom)		Marshall Swindell			
4. Company/Product (Name) Tolcide PS352C		PM# 33	X None Restricted		
10000 155520	}	33	,		
5. Name and Address of Applicant (Inclu	ude ZIP Code)	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(I), my product is			
Albright & Wilson UK Limited		similar or identical in composition and labeling to:			
210-222 Hagley Road West Oldbury, Warley		EPA Reg. No			
West Midlands, United Kingdon	1 B68 ONN				
Check if this is a new a		Product Name			
Check if this is a new a	uur 0333	Continue IV			
		Section - II			
Amendment - Explain below.			to Agency letter dated		
Resubmission in response to Ager	ncy letter dated	("Me Too" Application			
Notification - Explain below.		Other - Explain below			
Explanation: Use additional pa	age(s) is necessary. (For S	ection I and Section II.)			
		rd "Corrosive" to the "Precautionary State			
word was inadvertently omitted	from previously approved	labels. Notification certification stateme	nt is attached.		
		O III			
		Section - III			
Material This Product Will Be Packs Child-Resistant Packaging	aged In: Unit Packaging	Water Soluble Packaging	2. Type of Container		
Yes*	Yes	Yes	Metal		
∏ No	No No	No No	Plastic		
*Certification must be		lo. per If "Yes" No. per	→ ≒		
submitted		ontainer Package wgt. Container	Glass		
			Paper (Specifical)		
3. Location of Net Contents Informatic	on 4. Size(s) Reta	il Container 5 Locati	Other (Specifiy)		
Label Contai	'	\ 	Label		
		On	labeling accompanying product		
6. Manner in Which Label is Affixed t	o Product Lithogr				
	Paper g				
	Stencil	ed			
		Section - IV			
1. Contact Point (Complete items direc	tly below for identification of ind	ividual to be contacted, if necessary, to process thi	s application)		
Name		tle	Telephore No. (Include Area Code)		
Eliot I. Harrison	(202) 793-3903				
	Certification		6. Pate Application Received		
I certify that the statements I have mad					
Signature		fine or imprisonment or both under applicable law			
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	J 3.	1100			
	l A	gent for Albright & Wilson UK Limited			
4. Typed Name	5.	Date	,		
Eliot I. Harrison	i r	ecember 9, 1998			

12/01/98, Page 1 of 2

# TOLCIDE® PS352C

### INDUSTRIAL ANTIMICROBIAL

ACTIVE INGREDIENT:	
Tetrakis(hydroxymethyl) phosphonium sulfate	35%
INERT INGREDIENTS:	. 65%
TOTAL:	

EPA Reg. No. 33677-5

EPA Est. 550-TX-2

# DANGER

#### STATEMENT OF PRACTICAL TREATMENT

If in eyes: Flush immediately with large amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If swallowed: Promptly drink large quantities of water. Do not induce vomiting. Avoid alcohol. Call a physician immediately. If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention. If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. Get medical attention. Prolonged or frequent skin contact may cause allergic reactions in some individuals.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

## PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if inhaled. Avoid breathing vapor. Remove contaminated clothing and wash before reuse. Harmful or fatal if swallowed. Avoid contamination of food.

#### **ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

#### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store this product in a cool, dry area away from direct sunlight and heat to avoid deterioration. In case of a spill, flood the area with large quantities of water.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent) all containers and offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or other procedures approved by state and local authorities.

Note: Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk and/or handling of this material, when such use and/or handling is contrary to label directions.

In case of emergency, call CHEMTREC at 1-800-424-9300

ALBRIGHT & WILSON

**ALBRIGHT & WILSON UK LIMITED** 

210-222 Hagley Road West • Oldbury, Warley • West Midlands • United Kingdom B68 0NN

12/01/98, Page 2 of 2

#### Product of the United Kingdom

#### **DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

#### PAPER MANUFACTURING (for control of bacteria, fungi and algae)

Not for use in manufacture of paper and paperboard products and adhesives that may come in contact with food.

Dosing: Additions should be made at a point in the system where mixing action is good, e.g. raw stock chest beater or mixing unit.

Add intermittently or continuously depending on mill conditions.

Intermittent Dosing: Add 70-1000 ppm of TOLCIDE PS352C based on total water volume or an equivalent based on dry weight of paper produced.

Continuous Dosing: Add 40-140 ppm of TOLCIDE PS352C based on total water volume or an equivalent based on dry weight of paper produced.

INDUSTRIAL AND/OR COMMERCIAL RECIRCULATING COOLING WATER SYSTEMS (for control of bacteria, fungi and algae)

Initial Slug Dose: Add 200-750 ppm of TOLCIDE PS352C based on total water volume. Repeat until control is obtained. Thereafter, add either Intermittently 75-300 ppm of TOLCIDE PS352C or Continuously 40-140 ppm of TOLCIDE PS352C per day.

Dirty systems must be cleaned prior to treatment.

### HEAT TRANSFER SYSTEMS (Evaporative Condensers, Dairy Sweetwater Systems, Hydrostatic Sterilizers and Retorts, Brewery and Other Pasteurizers, and Warmers)

Add TOLCIDE PS352C at the same application rates, and in the same manner as described above. It should be added to the system at a point of uniform mixing such as a basin area, sump area, or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the system.

#### AIR WASHER SYSTEMS

For control of bacteria and fungi. Pre-clean the system with detergent and allow air washer to run with fan on for two hours. Flush and check nozzles, manually cleaning as necessary. Add 75-200 ppm of TOLCIDE PS352C at a point where uniform mixing and even distribution will occur. Repeat as needed to maintain control.

#### SOLUTIONS / EMULSIONS

Not for use in manufacture of paper and paperboard products and adhesives that may come in contact with food. For the preservation of solutions, emulsions, adhesives and other aqueous liquid products, the addition of 0.05% to 0.5% of TOLCIDE PS352C is effective. Add at a point in the processing system where there will be sufficient time and agitation for good mixing and dispersion. The exact amount of TOLCIDE PS352C to be added for the preservation of given formulations will depend on the components as well as local storage time and requirements.

#### OIL FIELD OPERATIONS

TOLCIDE PS352C is effective in controlling sulfate reducing bacteria, general aerobic bacteria, processing and distribution applications and supporting systems; such as injection water, water holding tanks, disposal well water, recirculating water handling systems, and pipelines. TOLCIDE PS352C has been shown to dissolve iron sulfide and sequester iron when used under these conditions, leading to improved filter life and well injectivity, and reduction of hydrocarbon sheen. TOLCIDE PS352C is also effective for use in controlling microbial growth in fluids used for drilling and stimulation of oil wells.

#### Water Floods

Tolcide PS352C should be added to a water flood system at a point where uniform mixing will occur.

Initial Treatment: For a noticeably fouled system, add 200-750 ppm TOLCIDE PS352C. When added to a flowing system, slug dose for 2-6 hours based on flow rates. Repeat as necessary until control is achieved.

<u>Subsequent Treatment</u>: Once control has been achieved, add 30-210 ppm TOLCIDE PS352C weekly or as needed to maintain control. When added to a flowing system, slug dose for 2-6 hours based on flow rates.

Continuous Treatment: TOLCIDE PS352C can be dosed continuously at a level of 30-143 ppm.

#### Oil and Gas Pipelines

TOLCIDE PS352C should be added at a point in the pipeline where uniform mixing will occur.

Slug Dosing: Follow instructions for water flood treatment.

Continuous Dosing: TOLCIDE PS352C can be dosed continuously at a level of 30-215 ppm.

#### Drilling Muds, Packer Fluids, Completion and Workover Fluids

TOLCIDE PS352C should be added to these fluids at a point where uniform mixing will occur. Add 70-3000 ppm of TOLCIDE PS352C to a freshly prepared fluid depending on severity of contamination.

TOLCIDE® is a registered trademark of Albright & Wilson UK Limited.

3 iP-1298

**NET CONTENTS: As Marked on Container**