

ALBRIGHT & WILSON

TOLCIDE® PS75LT

FOR THE CONTROL OF MICROBIAL CONTAMINATION
IN THE OIL PRODUCTION INDUSTRY

Active Ingredient:

Tetrakis(hydroxymethyl) phosphonium sulfate 75%
Inert Ingredients: 25%
Total: 100%

EPA Reg. No. 33677-7

EPA Est. 550-TX-2

KEEP OUT OF REACH OF CHILDREN
DANGER

STATEMENT OF PRACTICAL TREATMENT

If in eyes: Flush immediately with large amounts of clean, cool water for at least 15 minutes. Get medical attention immediately.

If swallowed: Promptly drink large quantities of water. Do not induce vomiting. Avoid alcohol. Call a physician immediately.

If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. Get medical attention.

Prolonged or frequent skin contact may cause allergic reactions in some individuals.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling.

Harmful or fatal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutants Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

TOLCIDE® is a registered trademark of ALBRIGHT & WILSON UK LIMITED.

Manufactured by:

ALBRIGHT & WILSON UK LIMITED

210-222 Hagley Road West

Oldbury, Warley

West Midlands, United Kingdom B68 0NN

Net Contents: As Marked on Container

ACCEPTED

JUL - 3 1997

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 33677-7

2 9 2

ALBRIGHT & WILSON

TOLCIDE® PS75LT

INDUSTRIAL ANTIMICROBIAL

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Storage: Store this product in a cool, dry area away from direct sunlight and heat to avoid deterioration. In case of a spill, flood the area with large quantities of water.

Pesticides Wastes: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture, or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent) all containers and offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE

It is violation of federal law to use this product in a manner inconsistent with its labeling.

ACCEPTED

JUL - 3 1997

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 33677-7

Oil Field Operations

TOLCIDE PS75LT is effective in controlling sulfate reducing bacteria, general aerobic bacteria, including microorganisms that contribute to biofilm formation in oil field recovery, processing and distribution applications and supporting systems; such as injection water, water holding tanks, disposal well water, recirculating water handling systems, and pipelines. TOLCIDE PS75LT is also effective for use in controlling microbial growth in fluids used for drilling and stimulation of oil wells.

Water Floods

TOLCIDE PS75LT should be added to a water flood system at a point where uniform mixing will occur.

Initial Treatment: For a noticeably fouled system, add 93-350 ppm TOLCIDE PS75LT. When added to a flowing system, slug dose for 2-6 hours based on flow rates. Repeat as necessary until control is achieved.

Subsequent Treatment: Once control has been achieved, add 14-98 ppm TOLCIDE PS75LT weekly or as needed to maintain control. When added to a flowing system, slug dose for 2-6 hours based on flow rates.

Continuous Treatment: TOLCIDE PS75LT can be dosed continuously at a level of 14-67 ppm.

Oil and Gas Pipelines

TOLCIDE PS75LT should be added at a point in the pipeline where uniform mixing will occur.

Slug Dosing: Follow instructions for water flood treatment.

Continuous Dosing: TOLCIDE PS75LT can be dosed continuously at a level of 14-100 ppm.

Drilling Muds, Packer Fluids, Completion and Workover Fluids

TOLCIDE PS75LT should be added to these fluids at a point where uniform mixing will occur. Add 33-1400 ppm TOLCIDE PS75LT to a freshly prepared fluid depending on severity of contamination.

Note: Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk and/or handling of this material, when such use and/or handling is contrary to label directions.