PM 31 - 33677-1

1/6/99

Page 17 4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JAN 0 6 1999

Albright & Wilson UK Limited 210-222 Hagley Road West Oldbury, Warley West Midlands, United Kingdom B68 ONN

Subject: Tolcide PS75LT

EPA Registration No. 33677-7 Notification Per PR-Notice 95-2

Your Notification Dated December 9, 1998

Dear Mr. Harrison:

)

This will acknowledge receipt of your notification to revise your label submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,

Marshall Swindell

Notification Coordinator

Regulatory Management Branch I Antimicrobials Division (7510C)

SYMBOL 75/UC
SURMANE P. Hoto

294

rieuse reuu insiructions on reverse bejore c	ompleting form. Form App	TOVEG, OMB NO	. 2070-0060, Approvai	expires 03-31-98	
EDA	United States		Registrat	ion	OPP Identifier Number
EPA Environ	ency Amendment			251532	
				231332	
Application for Pesticide - Section 1					
Company/Product Number 33677-7		2. EPA Product Manager			3. Proposed Classification
33077-7		Marshall Swindell			
4. Company/Product (Name)		PM#			
Tolcide PS75LT		33	1		X None Restricted
5. Name and Address of Applicant (Include ZIP Code)		6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(1), my product is			
Albright & Wilson UK Limited		similar or identical in composition and labeling to:			
210-222 Hagley Road West		EPA Reg. No.			
Oldbury, Warley West Midlands, United Kingdom B68 ONN					
· —	Product Name				
Check y into is a new aduresss					
Section - II					
Amendment - Explain below.		Final printed labels in response to Agency letter dated			
Resubmission in response to Agen		"Me Too" Application			
Notification - Explain below.		Other - Explain below			
Explanation: Use additional page(s) is necessary. (For Section I and Section II.)					
Notification per PR Notice 95-2. Notification adds the word "Corrosive" to the "Precautionary Statements" section of the label. This					
word was inadvertently omitted from previously approved labels. Notification certification statement is attached.					
<u> </u>					
Section - III					
1. Material This Product Will Be Pack					
Child-Resistant Packaging	Unit Packaging	{	Water Soluble Packaging		2. Type of Container
Yes*	Yes		Yes		Metal
∐ No	☐ No		No		Plastic
*Certification must be	If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt.	No. per Container	Glass
submitted	Ont rackaging wgt.	container	rackage wgi.	Container	Paper
<u> </u>					Other (Specifiy)
3. Location of Net Contents Information	letail Container		5. Location of	Label Directions	
Label Container			On Labe		
				On labelin	g accompanying product
6. Manner in Which Label is Affixed to Product Lithograph					
Paper glued Stenciled					
Section - IV					
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application)					
Name	Title Telephone No. (Include Area Code				
Eliot I. Harrison Agent for Albright & Wilson UK Limited (202) 393-3903 Certification 6. Date Application Received					
Certification 1 certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge					
that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law, , , , , , (Stamped)					
2. Signature		3. Title	· · · · · · · · · · · · · · · · · · ·		, , , , , , , , , , , , , , , , , , , ,
1 Stall				115	I: 3000
- loy		Agent for Al	lbright & Wilson U	K Limited	√
4. Typed Name		5. Date		1 2 2 1	
Eliot I. Harrison	į	December 9	, 1998		1 '

TOLCIDE® PS75LT

INDUSTRIAL ANTIMICROBIAL

EPA Reg. No. 33677-7

EPA Est. 550-TX-2

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

If in eyes: Flush immediately with large amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If swallowed: Promptly drink large quantities of water. Do not induce vomiting. Avoid alcohol. Call a physician immediately. If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. Get medical attention. Prolonged or frequent skin contact may cause allergic reactions in some individuals.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For quidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store this product in a cool, dry area away from direct sunlight and heat to avoid deterioration. In case of a spill, flood the area with large quantities of water.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent) all containers and offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or other procedures approved by state and local authorities.

Note: Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk and/or handling of this material, when such use and/or handling is contrary to label directions.

in case of emergency, call CHEMTREC at 1-800-424-9300

ALBRICHT & WILSON

ALBRIGHT & WILSON UK LIMITED

210-222 Hagley Road West • Oldbury, Warley • West Midlands • United Kingdom B68 0NN

Product of the United Kingdom

12/01/98, Page 2 of 2

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

OIL FIELD OPERATIONS

TOLCIDE PS75LT is effective in controlling sulfate reducing bacteria, general aerobic bacteria, processing and distribution applications and supporting systems; such as injection water, water holding tanks, disposal well water, recirculating water handling systems, and pipelines. TOLCIDE PS75LT has been shown to dissolve iron sulfide and sequester iron when used under these conditions, leading to improved filter life and well injectivity, and reduction of hydrocarbon sheen. TOLCIDE PS75LT is also effective for use in controlling microbial growth in fluids used for drilling and stimulation of oil wells.

Water Floods

Tolcide PS75LT should be added to a water flood system at a point where uniform mixing will occur.

Initial Treatment: For a noticeably fouled system, add 93-350 ppm TOLCIDE PS75LT. When added to a flowing system, slug dose for 2-6 hours based on flow rates. Repeat as necessary until control is achieved.

<u>Subsequent Treatment</u>: Once control has been achieved, add 14-98 ppm TOLCIDE PS75LT weekly or as needed to maintain control. When added to a flowing system, slug dose for 2-6 hours based on flow rates.

Continuous Treatment: TOLCIDE PS75LT can be dosed continuously at a level of 14-67 ppm.

Oil and Gas Pipelines

TOLCIDE PS75LT should be added at a point in the pipeline where uniform mixing will occur.

Slug Dosing: Follow instructions for water flood treatment.

Continuous Dosing: TOLCIDE PS75LT can be dosed continuously at a level of 14-100 ppm.

Drilling Muds, Packer Fluids, Completion and Workover Fluids

TOLCIDE PS75LT should be added to these fluids at a point where uniform mixing will occur. Add 33-1400 ppm of TOLCIDE PS75LT to a freshly prepared fluid depending on severity of contamination.

TOLCIDE® is a registered trademark of Albright & Wilson UK Limited.

33A-1298

NET CONTENTS: As Marked on Container

ş