

3 3677-7

9/12/2012

1/8

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D C 20460



United States
Environmental Protection
Agency

Office of Pesticide Programs

Rhodia, Inc
8 Cedar Brook Drive
Cranbury, N J 08512-3717

SEP 12 2012

AGENT Delta Analytical
12510 Prosperity Drive, Suite 160
Silver Spring, MD 20904

Attention Cristina Griffin, Agent

Subject Tolcide® PS75LT
EPA Registration No 33677-7
Notification Dated August 20, 2012

This will acknowledge receipt of your, submitted under the provisions of
FIFRA Section 3(c)(9)

Proposed Notification

- To add reader's notes to footer of label

General Comment

Based on a review of the submitted material, the following comments apply

The Notification is in compliance with PR Notice 98-10 and is acceptable
This information has been added to your file

If you have any questions or comments concerning this letter, please contact
Martha Terry at (703) 308-6217

Sincerely,

A handwritten signature in black ink, appearing to read "Marshall Swindell".

Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)

**EPA**
 United States
Environmental Protection Agency
 Washington DC 20460

☐ Registration
☐ Amendment
☒ Other

OPP Identifier Number

NOTIF**Application for Pesticide - Section I**1 Company/Product Number **33677-7**2 EPA Product Manager
Marshall Swindell

3 Proposed Classification

☐ None ☐ Restricted4 Company/Product (Name) **Rhodia UK Limited / Tolcide® PS75LT**PM# **33**

5 Name and Address of Applicant (Include ZIP Code)

Rhodia UK Limited
c/o Delta Analytical Corp
12510 Prosperity Drive, Suite 160
Silver Spring, MD 20904

Check if this is a new address

6 **Expedited Review** In accordance with FIFRA Section 3(c)(3)(b)(i) my product is similar or identical in composition and labeling to

EPA Reg No _____

Product Name _____

Section - II☐ Amendment Explain below☐ Resubmission in response to Agency letter dated _____☒ Notification Explain below☐ Final printed labels in response to Agency letter dated _____☐ Me Too Application☐ Other explain below**Explanation** Use additional page(s) if necessary (For section I and Section II)**Notification per PR Notice 98-10 to add reader's notes to footer of label**

This notification is consistent with the provisions of PR Notice 98 10 and EPA regulations at 40 CFR 152 46 and no other changes have been made to the labeling or the confidential statement of formula of this product I understand that it is a violation of 18 U S C Sec 1001 to willfully make any false statement to EPA I further understand that if this notification is not consistent with the terms of PR Notice 98 10 and 40 CFR 152 46 this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA

Section - III**1 Material this Product will be Packaged in**

Child Resistant Packaging

☐ Yes
☐ No

Unit Packaging

☐ Yes
☐ No

Water Soluble Packaging

☐ Yes
☐ No

2 Type of Container

☐ Metal
☐ Plastic☐ Glass☐ Paper☐ Other (Specify) _____*** Certification must be submitted**
 If Yes
 Unit Package wgt No per container

 If Yes
 Unit Package wgt No per container

3 Location of Net Contents Information

☐ Label ☐ Container

4 Size(s) of Retail Container

5 Location of Label Direction

☐ On Label
☐ On Labeling accompanying product

6 Manner In Which Label Is Affixed to Product

☐ Lithograph
☐ Paper glued
☐ Stenciled☐ Other _____**Section - IV**

1 Contact Point (Complete items directly below for identification of individual to be contacted if necessary to process this application)

Name

Cristina Griffin

Title

Agent for Rhodia UK Limited

Telephone No (Include Area Code)

301-680-7971**Certification**

I certify that the statements I have made on this form and all attachments thereto are true accurate and complete I acknowledge that any kind of knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law

2 Signature

3 Title

Agent for Rhodia UK Limited

4 Typed Name

Cristina Griffin

5 Date

August 20, 2012

6 Date Application Received

(Stamped)

3/8



August 20 2012

Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504P)
Environmental Protection Agency
One Potomac Yard
2777 S Crystal Drive Room S-4900
Arlington VA 22202

Attn Marshall Swindell PM 33

Re Notification per PR Notice 98-10 to add reader's notes to footer of label
Product Tolcide® PS75LT
EPA Reg No 33677-7
Company Rhodia UK Limited

Dear Mr Swindell

On behalf of Rhodia UK Limited I am submitting a notification per PR Notice 98-10 to add reader's notes to the footer of the label for Tolcide® PS75LT EPA Reg No 33677-7 This is the only change to the label since the last EPA approved label dated 10/18/11 The reader's notes are highlighted and appear as follows

[In the text 'this product' or alternate brand name may be substituted for Tolcide®PS75LT product name] [Information in brackets] is optional or instructional, italics in brackets indicate instructions not part of labeling]

This addition of reader's notes is being submitted as a notification for all 7 Rhodia Tolcide labels (EPA Company No 4564 and 33677)

Enclosures

- EPA form 8570-1
- 1 copy of the revised label with changes highlighted

If you have any questions regarding this submission please contact me at 301-680-7971 or cgriffin@delta-ac.com

Sincerely,



Cristina Griffin
Agent for Rhodia

Enclosures

cc Judith Kranetz Rhodia
12510 Prosperity Drive Suite 160 Silver Spring Maryland 20904
(301) 680 7971 fax (301) 680 7975 www.delta-ac.com

4/8

TOLCIDE® PS75LT

INDUSTRIAL ANTIMICROBIAL

ACTIVE INGREDIENT	
Tetrakis(hydroxymethyl) phosphonium sulfate	75%
OTHER INGREDIENTS	25%
TOTAL	100%

EPA Reg No 33677 7

EPA Est 80347 TX 1

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID	
If in eyes	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15 20 minutes• Remove contact lenses if present after the first 5 minutes then continue rinsing eye• Call a poison control center or doctor for treatment advice
If swallowed	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice• Have person sip a glass of water if able to swallow• Do not induce vomiting unless told to do so by a poison control center or doctor• Do not give anything by mouth to an unconscious person
If inhaled	<ul style="list-style-type: none">• Move person to fresh air• If person is not breathing call 911 or an ambulance then give artificial respiration preferably mouth to mouth if possible• Call a poison control center for further treatment advice
If on skin or clothing	<ul style="list-style-type: none">• Take off contaminated clothing• Rinse skin immediately with plenty of water for 15 20 minutes• Call a poison control center or doctor for treatment advice
Have the product container or label with you when calling a poison control center or doctor or going for treatment For emergency information call the National Pesticides Information Center at 1 800 858 7378 7 30 AM to 3 30 PM Pacific time (PT) Mon – Fri During other times call the poison control center at 1 800 222 1222 Note to physician Probable mucosal damage may contraindicate the use of gastric lavage	

See side panels for additional Precautionary Statements

In case of emergency call CHEMTREC at 1-800-424 9300

Manufactured for



RHODIA UK Limited
Trinity Street – Oldbury
West Midlands – United Kingdom B69 4WD
609 860-4000

Active ingredient produced in the United Kingdom and/or China

NET CONTENTS As Marked on Container

[Box and bullet format for First Aid section is optional]

[In the text this product or alternate brand name may be substituted for Tolcide®PS75LT product name]
[[Information in brackets] is optional or instructional italics in brackets indicate instructions not part of labeling]

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER Corrosive Causes irreversible eye damage May be fatal if swallowed Harmful if inhaled Harmful if absorbed through skin Do not get in eyes on skin or on clothing Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals Avoid breathing vapor or spray Wear long sleeved shirt and pants or coveralls goggles or face shield and chemical resistant gloves when handling Wash thoroughly with soap and water after handling and before eating drinking chewing gum using tobacco or using the toilet Remove and wash contaminated clothing before reuse

ENVIRONMENTAL HAZARDS

This product is toxic to fish Do not discharge effluent containing this product into lakes streams ponds estuaries oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority For guidance contact your State Water Board or Regional Office of the EPA

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling Not for use in paint

OIL FIELD AND PETROCHEMICAL OPERATIONS

TOLCIDE® PS75LT is effective in controlling sulfate reducing bacteria general aerobic bacteria including microorganisms that contribute to biofilm formation in oil field recovery processing and distribution applications and supporting systems such as injection water water holding tanks disposal well water recirculating water handling systems and pipelines TOLCIDE® PS75LT has been shown to dissolve iron sulfide and sequester iron when used under these conditions leading to improved filter life and well injectivity and reduction of hydrocarbon sheen TOLCIDE® PS75LT is also effective for use in controlling microbial growth in fluids used for drilling and stimulation of oil wells

Water Floods [Not for use in California]

TOLCIDE® PS75LT should be added to a water flood system at a point where uniform mixing will occur

Initial Treatment For a noticeably fouled system add 93 350 ppm TOLCIDE® PS75LT (70 262 5 ppm THPS) When added to a flowing system slug dose for 2 6 hours based on flow rates Repeat as necessary until control is achieved

Subsequent Treatment Once control has been achieved add 7 5 98 ppm TOLCIDE® PS75LT (5 73 5 ppm THPS) weekly or as needed to maintain control When added to a flowing system slug dose for 2-6 hours based on flow rates

Continuous Treatment TOLCIDE® PS75LT can be dosed continuously at a level of 7 5-67 ppm (5 50 ppm THPS)

Hydraulic Fracturing [Not for use in California]

TOLCIDE® PS75LT should be added to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down hole Add 66 7 350 ppm of TOLCIDE PS75LT (50 262 5 ppm THPS) depending on the degree of bacterial fouling in the source water

Oil and Gas Production and Transmission Pipelines and Systems

TOLCIDE® PS75LT should be added at a point in the pipeline where uniform mixing will occur The application should be conducted to ensure maximum distribution of TOLCIDE® PS75LT through the entire internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates

Slug Dosing Follow instructions for water flood treatment

Continuous Dosing TOLCIDE® PS75LT can be dosed continuously at a level of 14 100 ppm (10 5 75 ppm THPS)

Drilling Muds Packer Fluids Completion and Workover Fluids

TOLCIDE® PS75LT should be added to these fluids at a point where uniform mixing will occur Add 33 1400 ppm of TOLCIDE® PS75LT (24 5 1050 ppm THPS) to a freshly prepared fluid depending on severity of contamination

Gas Storage Well and Systems [Not for Use in California]

Individual injection wells should be treated with TOLCIDE® PS75LT at the same application rates and in the same manner as described under Water Floods Injections should be repeated as needed to maintain control

Individual drips should be treated with a sufficient quantity of TOLCIDE® PS75LT to produce a concentration of 33 3 133 3 ppm TOLCIDE® PS75LT (25 100 ppm THPS) when diluted by the water present in the drip Injections should be repeated as needed to maintain control

Well Remediation Operations [Not for Use in California]

Individual production or injection wells may be bullheaded with TOLCIDE® PS75LT to control bacteria and simultaneously dissolve iron sulfide deposits The TOLCIDE® PS75LT will be pumped into the well as a solution in water containing from 13 33% to 40% TOLCIDE® PS75LT (10% 30% THPS) The well is shut in for a period of time (at least 6 hours) then put back into operation

Hydrotesting

Water used to hydrotest pipelines or vessels should contain 66 6 666 5 ppm TOLCIDE® PS75LT (50 500 ppm THPS) depending on water quality and length of time the equipment will remain idle

[In the text this product or alternate brand name may be substituted for Tocide®PS75LT product name]

[[Information in brackets] is optional or instructional italics in brackets indicate instructions not part of labeling]

Pipeline Pigging and Scraping Operation

Add TOLCIDE® PS75LT to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper and a trailing pig) Sufficient TOLCIDE® PS75LT should be added to produce a concentration of 0.007% to 0.07% (50-500 ppm THPS) in the water at the discharge point or pig trap depending on the length of the pipeline and the severity of the biofouling

FIRE PROTECTION SYSTEMS

TOLCIDE® PS75LT is effective at controlling microbial growth in waters and on pipe surfaces in fire protection systems. Such microbial growth when combined with other forms of corrosion can lead to accelerated corrosion rates and pitting corrosion commonly referred to as microbiologically influenced corrosion. TOLCIDE® PS75LT also removes free oxygen from the water thus eliminating an important nutrient for bacteria and an important reactant in many corrosion reactions.

TOLCIDE® PS75LT should be added to a fire protection system using a chemical metering pump capable of variable pump rates. The TOLCIDE® PS75LT should be injected at a point such as a riser, manifold or makeup feed water line where uniform mixing and distribution will occur. Add 100-400 ppm TOLCIDE® PS75LT (75-300 ppm THPS) depending on severity of microbial contamination in the system. Repeat as needed.

SOLUTIONS / EMULSIONS

Not for use in manufacture of paper and paperboard products and adhesives that may come in contact with food. For the preservation of solutions, emulsions, adhesives and other aqueous liquid products, the addition of 0.0233% to 0.233% of TOLCIDE® PS75LT (0.0175% to 0.175% THPS) is effective. Add at a point in the processing system where there will be sufficient time and agitation for good mixing and dispersion. The exact amount of TOLCIDE® PS75LT to be added for the preservation of given formulations will depend on the components as well as local storage time and requirements.

PAPER AND PAPERBOARD MANUFACTURING (for control of bacteria, fungi and algae)

a) For use as a slimicide in the manufacture of paper and paperboard products and adhesives that do not contact food

Dosing: Additions should be made at a point in the system where mixing action is good, e.g. raw stock chest beater or mixing unit. Add intermittently or continuously depending on mill conditions.

Intermittent Dosing: Add 32-66-466-55 ppm of TOLCIDE® PS75LT (24-5-350 ppm THPS) based on total water volume or an equivalent based on dry weight of paper produced.

Continuous Dosing: Add 18-66-65-3 ppm of TOLCIDE® PS75LT (14-49 ppm THPS) based on total water volume or an equivalent based on dry weight of paper produced.

b) For use as a slimicide in the manufacture of paper and paperboard products that may contact food

Dosing: Additions should be made at a point in the system where mixing action is good, e.g. raw stock chest beater or mixing unit.

Add intermittently or continuously depending on mill conditions.

Intermittent Dosing: Add 32-66-112 ppm of TOLCIDE® PS75LT (24-5-84 ppm THPS) based on total water volume or an equivalent based on dry weight of paper produced. The maximum use concentration of THPS in the slurry cannot exceed 84 ppm.

Continuous Dosing: Add 18-66-65-33 ppm of TOLCIDE® PS75LT (14-49 ppm THPS) based on total water volume or an equivalent based on dry weight of paper produced. The maximum use concentration of THPS in the slurry cannot exceed 84 ppm.

c) For use as a preservative for Alkyl Ketene Dimer (AKD) Emulsions

This product can be used to prevent bacterial and fungal contamination of AKD emulsions that are applied to food contact paper and paperboard at the dry end of the paper machine.

Dosing: Apply from 233-33-662-66 ppm of TOLCIDE® PS75LT (175-497 ppm THPS) to the AKD emulsion to be preserved.

d) For use as a preservative to retard microbial growth in water based coatings, starches, pigments and filler slurries
Do not use in paper and paperboard and adhesives that will contact food [Not for Use in California]

The treatment rate necessary to retard spoilage of the additive will vary with the extent of contamination of make up water and the length of storage.

Dosing: Apply from 233-33-666-5 ppm of TOLCIDE® PS75LT (175-500 ppm THPS) to the additive to be preserved based on the total weight of the additive and water.

INDUSTRIAL FRESH WATER SYSTEMS [Not for Use in California]

TOLCIDE® PS75LT is effective in controlling algae in holding ponds and in controlling bacteria and fungi in holding and processing tanks of industrial fresh water systems supplying water to pulp and paper mills, textile mills and other manufacturing plants. In pulp and paper mills, treatment of the fresh water with TOLCIDE® PS75LT can make an important contribution to slime control. The use of TOLCIDE® PS75LT as described will reduce the development of slime in fresh water pipes and other equipment and on the pulp and paper mill machine parts contacted by fresh water. If water is used in the manufacture of paper and paperboard products that may contact food, the concentration of THPS in the slurry can not exceed 84 ppm.

For the control of algae in industrial fresh water systems, TOLCIDE® PS75LT should be added to provide a concentration of 1-33-13-33 ppm of product (1-10 ppm of THPS). Treatment should be based on the amount of water entering a pond or reservoir or leaving the pond or reservoir and entering the immediate processing operations. While treatment can be made continuously, regular slug dosing treatment will provide adequate control.

[In the text 'this product' or alternate brand name may be substituted for Tolcide®PS75LT product name]

[[Information in brackets]] is optional or instructional. Italics in brackets indicate instructions not part of labeling.]

INDUSTRIAL WASTEWATER SYSTEMS (Wastewater Systems Wastewater Sludge and Wastewater Holding Tanks)
[Not for Use in California]

TOLCIDE® PS75LT should be added to a wastewater system or sludge at a convenient point of uniform mixing such as digester
Slug Dosing Add 53 3 350 ppm of TOLCIDE® PS75LT (40 262 5 ppm THPS) per 1 000 gallons of wastewater or sludge
Continuous Dosing Add 1 3 26 6 ppm TOLCIDE® PS75LT (1 20 ppm THPS) per 1 000 gallons of wastewater or sludge

MACROFOULING CONTROL [Not for Use in California]

TOLCIDE® PS75LT should be added continuously to maintain a level of 20 ppm active ingredient (THPS) in the system for a period of at least 96 hours **Initial Dose** When macrofouling is present in the system apply 26 66 ppm of TOLCIDE® PS75LT (20 ppm THPS) based on total water volume Continue to add TOLCIDE® PS75LT as needed to maintain the 20 ppm active ingredient (THPS) level for a period of at least 96 hours

INDUSTRIAL AND/OR COMMERCIAL RECIRCULATING COOLING WATER SYSTEMS (for control of bacteria fungi and algae)

Note For cooling water systems of equal to or greater than 4000 gallons do not apply by open pouring of liquid to cooling water systems a metering pump delivery system is required for this use and application method

Initial Slug Dose Add 53 3 350 ppm of TOLCIDE® PS75LT (40 262 5 ppm THPS) for 2 6 hours based on total water volume Repeat until control is obtained Thereafter add either **Intermittently** 35 140 ppm of TOLCIDE® PS75LT (26 105 ppm THPS) or **Continuous Dosing** 18 66-65 33 ppm of TOLCIDE® PS75LT (14 49 ppm THPS) per day Dirty systems must be cleaned prior to treatment

HEAT TRANSFER SYSTEMS (Evaporative Condensers Dairy Sweetwater Systems Hydrostatic Sterilizers and Retorts Brewery and Other Pasteunizers and Warmers)

Add TOLCIDE® PS75LT at the same application rates and in the same manner as described above It should be added to the system at a point of uniform mixing such as a basin area sump area or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the system

SERVICE WATER AND AUXILLIARY SYSTEMS

TOLCIDE® PS75LT should be added to service water and auxiliary systems at the same application rates and in the same manner as described above It should be added to the system at a point of uniform mixing such as a basin area sump area or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the system

STORAGE AND DISPOSAL

[For rigid non refillable containers 5 gallons or less]

Do not contaminate water food or feed by storage or disposal

STORAGE Store this product in a cool dry area away from direct sunlight and heat to avoid deterioration In case of a spill flood the area with large quantities of water

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance

CONTAINER HANDLING AND DISPOSAL Nonrefillable container Do not reuse or refill this container Offer for recycling or reconditioning if appropriate Triple rinse or pressure rinse container (or equivalent) promptly after emptying Triple rinse as follows Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip Fill the container ¼ full with water and recap Shake for 10 seconds Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal Drain for 10 seconds after the flow begins to drip Repeat this procedure two more times Pressure rinse as follows Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal Insert pressure rinsing nozzle in the side of the container and rinse at about 40 PSI for at least 30 seconds Drain for 10 seconds after the flow begins to drip

[In the text 'this product' or alternate brand name may be substituted for Tocide®PS75LT product name]

[[Information in brackets] is optional or instructional italics in brackets indicate instructions not part of labeling]

8/8

[For rigid nonrefillable containers greater than 5 gallons]

Do not contaminate water food or feed by storage or disposal

STORAGE Store this product in a cool dry area away from direct sunlight and heat to avoid deterioration In case of a spill flood the area with large quantities of water

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance

CONTAINER HANDLING AND DISPOSAL Nonrefillable container Do not reuse or refill this container Offer for recycling or reconditioning if appropriate Triple rinse or pressure rinse container (or equivalent) promptly after emptying Triple rinse as follows Empty the remaining contents into application equipment or a mix tank Fill the container ¼ full with water Replace and tighten closures Tip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds Stand the container on its end and tip it back and forth several times Turn the container over onto its other end and tip it back and forth several times Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal Repeat this procedure two more times Pressure rinse as follows Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal Insert pressure rinsing nozzle in the side of the container and rinse at about 40 PSI for at least 30 seconds Drain for 10 seconds after the flow begins to drip

[For refillable containers]

Do not contaminate water food or feed by storage or disposal

STORAGE Store this product in a cool dry area away from direct sunlight and heat to avoid deterioration In case of a spill flood the area with large quantities of water

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance

CONTAINER HANDLING AND DISPOSAL Refillable container Refill this container with THPS only Do not reuse this container for any other purpose Pressure rinsing the container before final disposal is the responsibility of the person disposing of the container Cleaning before refilling is the responsibility of the refiller Pressure rinse the container for final disposal as follows Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal Insert pressure rinsing nozzle in the side of the container and rinse at about 40 PSI for at least 30 seconds Drain for 10 seconds after the flow begins to drip

[For Bulk Shipment Transport Vehicles Note In accordance with 40CFR 156 (e) bulk shipment transport vehicles are exempt from the requirements for container handling and disposal therefore only pesticide storage and disposal is required on bulk transport vehicle labeling]

Do not contaminate water food or feed by storage or disposal

STORAGE Store this product in a cool dry area away from direct sunlight and heat to avoid deterioration In case of a spill flood the area with large quantities of water

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance

[All products must bear a batch code This is a lot number or other code used by the registrant or producer to identify the batch of the pesticide product distributed and sold Location may be on the container or the label]

Note To the extent consistent with applicable law seller makes no warranty expressed or implied concerning the use of this product other than indicated on the label To the extent consistent with applicable law buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label directions

TOLCIDE® is a registered trademark of Rhodia UK Limited

[In the text this product or alternate brand name may be substituted for Tolcide®PS75LT product name]

[[Information in brackets]] is optional or instructional italics in brackets indicate instructions not part of labeling]