

CHEMITROL ALGAECIDE

COMPOSITION

Percent by weight

Active ingredient..... 15.0 percent
*Poly [oxyethylene (dimethyliminio) ethylene
(dimethylimino)-Ethylene dichloride]*
Inert ingredient..... 85.0 percent
Weight per gallon..... 8.58 pounds
Weight of active ingredient per gallon.... 1.29 pound

APPLICATION

CHEMITROL ALGAECIDE is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of CHEMITROL ALGAECIDE per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of CHEMITROL ALGAECIDE based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.0 to 10.0 fluid ounces of CHEMITROL ALGAECIDE per 1000 gallons of water (8 to 80 parts per million of CHEMITROL ALGAECIDE) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not discharge treated effluent where it will drain into lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

MANUFACTURED BY

ANDERSON WATER ENGINEERING CO.

843 W. Monroe Street
Chicago, Illinois 60607

EPA Reg. No. 34144-1

July 22, 1974

34144-1

34144-1