

ACCEPTED

NOV 7 1974

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED UNDER NO SUBJECT
TO ATTACHED COMMENTS.

APPLICATION

CR 505 PLUS ALGAERITE is used to control algae. bacteria. and fungi in recirculating commercial and industrial water cooling towers. Prior to its use. systems must be cleaned to remove algal growth. microbiological slime and other deposits. An initial slug addition of 2.9 to 7.3 fluid ounces of CR 505 PLUS ALGAERITE per 1000 gallons of water to provide a concentration of 24 to 60 parts per million of CR 505 PLUS ALGAERITE based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.73 to 7.3 fluid ounces of CR 505 PLUS ALGAERITE per 1000 gallons of water (6 to 60 parts per million of CR 505 PLUS ALGAERITE) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Chemile 1

CR-505 PLUS ALGAERITE

Manufactured By
CHEMRITE CORPORATION

EPA REG. #34224-1

NET CONTENTS

12600 SOUTH DAPHNE AVENUE HAWTHORNE, CALIFORNIA 90250

CAUTION: Keep out of reach of children

Chemile.

CR-505 PLUS ALGAERITE

	Percent by weight
Active Ingredients Poly(oxyethylene (dimethyliminio) ethylene (dimethyliminio)- ethylene dichloride)	
Weight per gallon	8.69 pounds

NET CONTENTS _____

Manufactured By
CHEMRITE CORPORATION
12600 SOUTH DAPHNE AVENUE
HAWTHORNE, CALIFORNIA 90250

EPA REG. #34224-1

CAUTION: Keep out of reach of children

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food

This product is toxic to fish. Do not discharge treated effluent where it will drain into lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.