

BETZ®

ENTECH, INC.

ENTECH 340

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

DANGER

MAY BE FATAL IF SWALLOWED. MAY BE ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATIONS. DO NOT GET INTO EYES, ON SKIN OR ON CLOTHING. DO NOT INHALE VAPORS OR MIST. USE WITH ADEQUATE VENTILATION. IMMEDIATELY REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING. AVOID STORAGE NEAR FOOD OR FEED PRODUCTS.

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND WILDLIFE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS ACTIVE INGREDIENT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS, OR PUBLIC WATERS UNLESS THIS PESTICIDE IS SPECIFICALLY IDENTIFIED AND ADDRESSED IN AN NPDES PERMIT. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PESTICIDE TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICE OF THE EPA. APPLY THIS PESTICIDE ONLY AS SPECIFIED ON THIS LABEL.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE. DO NOT USE, POUR OR STORE NEAR HEAT OR OPEN FLAME.

Active Ingredients:

N-Alkyl (C12-5Z, C14-60Z, C16-30Z, C18-5Z) dimethyl benzyl ammonium chloride.....	24.0Z
Bis (tributyltin) oxide.....	5.0Z
Inert Ingredients w:.....	71.0Z
Total.....	100.0Z

* Inert ingredients include solubilizing and dispersing agents.

CONTENTS: LIQUID
POUNDS PER GALLON: 8.2 (65F)
EPA REG. NO.: 34571-1

EPA EST. NO.

DANGER

KEEP OUT OF REACH OF CHILDREN STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash immediately with plenty of soap and water. Consult physician.

In case of contact with eyes, flush promptly and thoroughly with clean water for 15 minutes. Immediately contact physician.

In case of ingestion, immediately contact physician.

A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.

DIRECTIONS FOR USE:

 It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

STORAGE: Keep container tightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are acutely hazardous and/or toxic. Improper disposal, spray mixture, or rinse is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your local Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: METAL AND PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and send to landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

FIBER DRUMS WITH LINERS: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into appropriate container. Dispose of liner and drum in a sanitary landfill or incinerate if allowed by state and local authorities. Do not reuse empty drum or liner.

RECIRCULATING COOLING WATER SYSTEMS

This product aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, commercial and industrial cooling towers, influent systems such as flow through filters, lagoons, industrial water scrubbing systems and brewery pasteurizers. This product may be added to the systems either continuously or intermittently or as needed. The frequency of feeding and duration of the treatment will depend upon the severity of the problem. **BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

FOR CONTROL OF BACTERIA, FUNGI AND ALGAE

INTERMITTENT OR SLUG METHOD—INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.2 to 1.0 pound (24 to 120 ppm) per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add this product at the rate of 0.1 to 0.75 pound (12 to 90 ppm) per 1000 gallons of water in the system every 3 days or as needed to maintain control.

CONTINUOUS FEED METHOD—INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.2 to 1.0 pound (24 to 120 ppm) per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: Continuously feed this product to maintain control at the rate of 0.1 to 0.75 pound (12 to 90 ppm) per 1000 gallons of water in the system.

AIR WASHERS—For use only in industrial air washer mist eliminating components. This product controls slimes in industrial air washer systems. Add this product at the rate of 0.2 to 1.0 pound (24 to 120 ppm) per 1000 gals of water in the system. Repeat until control is achieved.

INTERMITTENT OR SLUG METHOD—INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.2 to 1.0 pound (24 to 120 ppm) per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add this product at the rate of 0.1 to 0.75 pound (12 to 90 ppm) per 1000 gallons of water in the system every 3 days or as needed to maintain control.

NET WT. LBS.
LOT NO.

FOR INDUSTRIAL USE. Technical advice regarding specific site problems is available from BETZ. 34571-1