

FILE:RELC153C.COM
SENT TO EPA 5/15/83

PTEL

BETZ

ENTEC 314

5/15/83

1 Direct
2 Indirect
3 In the Pesticide
4 In the Label

(FIRST PANEL)

PRECAUTIONARY STATEMENTS[14bf]

HAZARDS TO HUMANS AND[12bf]
DOMESTIC ANIMALS[12bf]

WARNING[18bf]

HARMFUL IF SWALLOWED. Causes eye and skin irritation. Do not get into eyes, on skin or on clothing. Do not inhale vapor or mist. Use with adequate ventilation. Wear goggles and face shield rubber gloves and protective clothing (hats, long sleeve shirt, long pants and boots) when handling. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS[14bf]

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public water unless in accordance with a NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of container and equipment or disposal of wastes. Apply this pesticide only as specified on this label.

DIRECTIONS FOR USE[14bf]

- It is a violation of Federal law to use this product in manner inconsistent with its labeling.

RECIRCULATING COOLING WATER SYSTEMS[12bf]

- BETZ Entec 314 aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, commercial and industrial cooling towers, influent systems such as flow through filters and launders, industrial water scrubbing systems and brewery pasteurizers.
- This product may be added to the system either continuously or intermitt-

After the first feeding, open one of the restriction boxes or some other point to insure uniform mixing. The frequency of feeding and duration of the treat-

ment will defend upon the severity of the problem.

(Directions for Use continued on
third panel.)

FNTEC033 8306

Business Phone: 215-674-9200 BETC Entec, ECorit, etc bottom of second panel.

(SECOND PANEL)

Contents: LIQUID

Active Ingredients:

Sodium dimethylidithiocarbamate.....15.0%

Nebam (Disodium ethylene bisdithiocarbamate).....15.0%

Inert Ingredients*.....70.0%

Total.....100.0%

* Insert ingredients include solubilizing and dispersing agents.

EPA Res. No. 34571-3

WEIGHT PER GALLON OF PRODUCT
9.7 Pounds (60F)

NET WEIGHT OR VOLUME
AS MARKED ON CONTAINER

KEEP OUT OF REACH OF CHILDREN [12b f]

WARNING[18bf]

STATEMENT OF PRACTICAL TREATMENT[14bf]

In case of contact with skin, wash immediately with plenty of soap and water. Immediately contact physician.

In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately contact physician.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not avail-

For medical information call 911.
Immediately contact physician.

See left panel for additional Precau-

tionary Statements.

116, HORSHAM, PENNSYLVANIA 19044 (cont'd at bottom of third panel.)

(THIRD PANEL)

BADLY FOULED SYSTEMS must be cleaned
before treatment if necessary.

FOR THE CONTROL OF BACTERIA AND FUNGI[12]

O INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ Entec 344 at the rate of 0.5 to 2.0 pound (60 to 240 ppm) per 1000 gallons of water in the system. Repeat until control is achieved.

O SUBSEQUENT DOSE: When microbial control is evident, add BETZ Entec 314 at the rate of 0.25 to 1.0 pound (30 to 120 ppm) per 1000 gallons of water in the system every 3 days or as needed to maintain control.

O CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ Entec 344 at the rate of 0.25 to 1.0 pound (30 to 120 ppm) per 1000 gallons of water in the system.

O SUBSEQUENT DOSE: Continuously feed BETZ Entec 344 to maintain a dose of 0.1 to 0.5 pound (12 to 60 ppm) per 1000 gallons of water in the system.

O FOR CONTROL OF ALGAE

O INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ Entec 344 at the rate of 0.5 to 2.0 pound (60 to 240 ppm) per 1000 gallons of water in the system. Repeat until control is achieved.

O SUBSEQUENT DOSE: When algal control is evident, add BETZ Entec 344 at the rate of 0.25 to 1.0 pound (30 to 120 ppm) per 1000 gallons of water in the system daily or as needed to maintain control.

O CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ Entec 344 at the rate of 0.25 to 1.0 pound (30 to 120 ppm)

BLST 1

31E

per 1000 gallons of water in the system.
Repeat until control is achieved.

SUBSEQUENT DOSE: Continuously feed BETZ

Entec 344 to maintain a dosage of 0.1 to 0.5 pound (12 to 60 ppm) per 1000 gallons of water in the system.

STORAGE AND DISPOSAL[12bf]

STORAGE: Keep container tightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

DISPOSAL: Do not contaminate water, food or feed by storage or disposal.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Metal and Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn if allowed by state and local authorities. If burned, stay out of smoke.

Fiber Drums with Liners: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner and drum in a sanitary landfill or incinerate if allowed by state and local authorities. Do not reuse empty drum or liner.

FOR COMMERCIAL AND INDUSTRIAL USE ONLY. Technical advice regarding specific site problems is available from BETZ Entec, Inc.

Emergency (Health or Accident): 215-355-3300

... 100E