

DANGER

Corrosive to eyes and mucous membranes. Do not get into eyes, on skin or clothing. In case of contact with eyes, wash with plenty of water, seek medical attention immediately. Irritating to nose and throat. May cause burns to broken skin. In case of contact, wash with soap and water. Wash hands before handling. Wear rubber gloves and face shield when handling.

WARNING. Keep material dry. If material gets wet it may decompose, liberating toxic gases. If this occurs, isolate container and flood with water. Avoid inhalation of released gases.

ENVIRONMENTAL PRECAUTIONS

Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty container. Send to drum reconditioner, or destroy by perforating or crushing and bury in a safe place.

DIRECTIONS FOR USE

BETZ ENTEC 343 aids in the control of fungi and bacteria in the water in brewery pasteurizers and in recirculating industrial water cooling towers.

In the case of brewery pasteurizers, this product should be used at a rate between 0.05 and 0.38 pound per thousand gallons of water per compartment.

In recirculating cooling tower systems, use at a rate between 0.1 and 0.5 pound per thousand gallons of water contained in the system. Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Apply at a point in the system where the pellets will dissolve uniformly. Repeat treatment everyday, or as needed. In the event the system is badly fouled, precleaning is recommended.

ELC 152 7505

STORE IN COOL DRY PLACE—KEEP CONTAINER COVERED



Measurement of the residual chlorine levels in the system should be made on a periodic basis to insure a 0.2 to 0.5 part per million (ppm) residual minimum.

FOR INDUSTRIAL USE ONLY. Technical advice regarding specific site problems is available from BETZ ENTEC, INC.

Contents: PELLET

Active Ingredient
1, 3-dichloro-5,
5-dimethylhydantoin
(provides 60.0% available chlorine)
Inert Ingredients*
*Inert ingredients include solubilizing
and dispersing agents.
EPA Reg. No. 34571-5
NET WEIGHT
As Marked on Container