

BETZ ENTEC 360

34571-11
ACCEPTED
JUL

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

HARMFUL OR FATAL IF SWALLOWED.
CORROSIVE. DO NOT TAKE INTERNALLY.

ENVIRONMENTAL HAZARDS

PHYSICAL AND CHEMICAL HAZARDS
CHEMICAL HAZARD: STRONG OXIDIZING
AGENT

Contents PELLETS

| | |
|---|------------------------|
| Active ingredient | |
| Sodium dichloro-s-triazinetrione dihydrate | 99.5% |
| Inert ingredients | 0.5% |
| Minimum available chlorine | 89% |
| EPA Reg. No. 34571-11 | |
| Net Weight and Volume | as marked on Container |

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

RECIRCULATING COOLING WATER SYSTEMS

BETZ Entec 360 aids in the control of bacterial, fungal and algal films in evaporative condensers, heat exchangers, water systems, commercial and industrial cooling towers, influent systems such as flow through, intake pipes, lagoons, etc., industrial water scrubbing systems and brewery pasteurizers. This product may be added to systems either continuously or intermittently or as required. The frequency of feeding and duration of the treatment will depend upon the severity of the problem.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

FOR CONTROL OF BACTERIA AND FUNGI

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.1 to 1.5 pound to 1000 gallons or 12 to 180 parts per million of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.05 to 1.0 pound to 1000 gallons or 6 to 120 parts per million of water in the system every 3 days or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.1 to 1.5 pound to 1000 gallons or 12 to 180 parts per million of water in the system.

SUBSEQUENT DOSE: Continuously feed to maintain a dosage of 0.05 to 1.0 pound to 1000 gallons or 6 to 120 parts per million of water in the system.

STORE IN A D

KEEP CONTAINER COVERED — DO NOT

2

DIRECTIONS FOR USE

RECIRCULATING COOLING WATER SYSTEMS

1. Add 100 ppm of the product to the cooling water system. The product will be distributed throughout the system by the circulating water.

2. Maintain the product concentration in the cooling water at 100 ppm. This can be done by adding the product to the cooling water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the cooling water system.

FOR CONTROL OF BACTERIA AND FUNGI

INTERMITTENT OR SLUG METHOD

1. Add 100 ppm of the product to the water. The product will be distributed throughout the water.

2. Maintain the product concentration in the water at 100 ppm. This can be done by adding the product to the water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the water.

CONTINUOUS FEED METHOD

1. Add 100 ppm of the product to the water. The product will be distributed throughout the water.

2. Maintain the product concentration in the water at 100 ppm. This can be done by adding the product to the water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the water.

FOR CONTROL OF BACTERIA AND FUNGI

1. Add 100 ppm of the product to the water. The product will be distributed throughout the water.

2. Maintain the product concentration in the water at 100 ppm. This can be done by adding the product to the water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the water.

CONTINUOUS FEED METHOD

1. Add 100 ppm of the product to the water. The product will be distributed throughout the water.

2. Maintain the product concentration in the water at 100 ppm. This can be done by adding the product to the water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the water.

STORAGE AND DISPOSAL

1. Store in a dry place. Do not store at elevated temperatures.

2. Keep container covered. Do not store at elevated temperatures.

3. Dispose of the product in accordance with the instructions on the label.

FOR INDUSTRIAL USE ONLY

1. Add 100 ppm of the product to the water. The product will be distributed throughout the water.

2. Maintain the product concentration in the water at 100 ppm. This can be done by adding the product to the water at a rate of 100 ppm per 100,000 gallons of water per day.

3. The product will be effective against bacteria and fungi in the water.

DANGER

STORE IN A DRY PLACE
KEEP CONTAINER COVERED DO NOT STORE AT ELEVATED TEMPERATURES