34688.26 PM 21

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460

NOTICE OF PESTICIDE: A REGISTRATION REREGISTRATION

(Under the Federal Insecticide, Fungicide and Rodentis ide Act, as amended)

EPA REGISTRATION NO. 34688-26

NOV 25 1985

TERM OF ISSUANCE
Conditional

NAME OF PESTICIDE PRODUCT

Intercide Copper Octoate 2% Wood
 Preservative - Water Repellent

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

 $\vdash$ 

interital Chemicals Inc. 600 Jers v Avenue 10% Brucewick, NJ - 08903 7

161 158438 18 1

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This project is conditionally requistered in accordance with ETFRA section  $3(\cos t7)(A)$  provided that we as

- 1. Swemit and/or cite all data required for registration/reregistration of your polluct under FTPRA coc. 3(c)(5) when the Agency requires all registrant. I implay products to cubmit such data.
- 2. Make the labeling change is ted below before you release the product for shapment.
  - a. Add the phrase "FPA Registration No. 34688-26."
  - b. Correct label ingredient statement to read 100%.
  - c. Under Storage and Disposal add statement for product storage intermation.
- 3. Submit tive (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

Hung M. Lacoly

DATE 1/25/8

EPA Form 8570-6 (Rev. 5-76)

PREVIOUS SPITION MAY BE SED UNTIL SUPPLY IS EXHAUSTED

88814:Forrest:RD-E4:KENCO:11/7/85:11/15/85:DKD:VO

If these conditions are not complied with, the registration will be subject to cancellation in accordance with PIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767)

Enclosure

## Front Panel

# INTERCIDE COPPER OCTOATE 2% WOOD PRESERVATIVE-WATER REPELLENT

A Ready-to-Use Fungicide for the Control of Mildew and Fungal Rot on Wood

Active Ingredient:

Copper 2-ethylhexanoate ......

(Copper as metal--2%)

Total

100.00%

11.02%

Keep Out of Reach of Children

100.85 // \( (12 pt)

CAUTION

(18 pt)

See Side Panel for Additional Precautionary Statements

EPA Reg. No. 34688-

EPA Est. No. 34688-NJ-1

Net Contents: 55 gals.

Interstab Chemicals, Inc. 500 Jersey Ave. -- PO Box 638 New Brunswick, NJ 08903

ACCEPTED
with COMMENTS
EPA Letter Dated:

NOV 2 5 1985

Under the Pederal boundede, Funcicide, and Research & Act as amended, for a composition of mediatered under a factor of

er er er

## Left Panel

#### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

#### CAUTION

(18 pt)

#### Contains Petroleum Distillate

Harmful if swallowed, inhaled or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling.

## Statement of Practical Treatment:

If in eyes, flush with plenty of water and get medical attention.

If swallowed, do not induce vomiting. Call a physician immediately.

If on skin, wash with plenty of soap and water.

#### ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

## PHYSICAL OR CHEMICAL HAZARDS

Combustible. Keep away from heat, sparks or open flame. Use with adequate ventilation.

## Right Panel

## Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

(12 pt)

Do not contaminate water, food, or feed by storage or disposal.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

## Instructions for Treating Wood

Intercide Copper Octoate 2% is a ready-to-use product containing Copper 2-ethylhexanoate. It contains a petroleum solvent and can be used for treating lumber and heavy timbers. Treatment of wood includes the following representative wooden items: wooden flooring for decks and patios, ladders, door and window frames and sashes, fence posts, stakes and small dimensional lumber, wooden siding and shingles, etc. It should be used on heavy structural timbers for above ground use only.

Dip Treatment: Lumber and small wooden structures should be totally immersed in Intercide Copper Octoate 2% treating solution for a period of from 30 seconds to 3 minutes depending on the thickness of the wood and the absorption required. Heavy lumber items should be dipped for 3 minutes, whereas light and absorptive stakes, window frames, etc. may be sufficiently treated in less time. The treated wood should be drained of excess solution and allowed to air dry until all solvent is gone and the wood is free from solvent odor. This usually takes 24 hours.

Brush Coating and Spraying: Intercide Copper Octoate 2% is ideal for brushing or spraying all types of wood items as illustrated above. When using a brush or spraying, coverage should be complete or until runoff starts to occur. After permitting to dry for 24 hours, a second coat may be in applied.

Treated dried wood may be painted over if desirable.

## Right Panel (cont)

This product contains a water repellent and may be used on any lumber where water repellency is desirable. Care should be taken in areas that are to be painted to insure that the dried surface can be properly painted. It is suggested that a trial be made on a small area before the product is used generally.

## Cleaning of Brushes or Spraying Equipment

Equipment and/or brushes may be cleaned with mineral spirits or a suitable paint thinner.