

INTERCID[®] COPPER OCTOATE 2% WOOD PRESERVATIVE-WD

10/1
Pms 1
3/1/87

EPA REG. No. 34688-27 EPA EST. No. 34688-NJ-1
A READY-TO-USE FUNGICIDE FOR THE CONTROL OF MILDEW AND FUNGAL ROT ON WOOD

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

CAUTION

Contains Petroleum Distillate

Harmful if swallowed, inhaled or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

- IF IN EYES: Flush with plenty of water and get medical attention.
- IF SWALLOWED: Do not induce vomiting. Call a physician immediately.
- IF ON SKIN: Wash with plenty of soap and water.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

ACCEPTED
FEB 1 1987
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 34688-27

ACTIVE INGREDIENT:

Copper 2-ethylhexanoate 11.02%
(Copper as metal...2%)

INERT INGREDIENTS: 88.98%

TOTAL 100.00%

KEEP OUT OF REACH OF CHILDREN CAUTION

SEE SIDE PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS

Net Contents: 55 Gals.

This information is furnished without warranty, representation, inducement of any kind, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose except that it is accurate to the best of Interstab Chemical's knowledge or obtained from sources believed by Interstab Chemicals to be accurate, and Interstab Chemicals does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product read its label.

Interstab Chemicals

500 JERSEY AVENUE, P.O. BOX 638
NEW BRUNSWICK, NJ 08903 (201) 247-2209

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

This product will freeze, do not store outside. Keep container tightly closed when not in use. Clean up spills with diatomaceous earth or similar substance followed by a thorough washing.

Do not contaminate water, food, or feed by storage or disposal. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

INSTRUCTIONS FOR TREATING WOOD

Intercide Copper Octoate 2% is a ready-to-use product containing Copper 2-ethylhexanoate. It is a water containing system and can be used for treating lumber and heavy timbers such as fence posts, poles, structural timbers, stakes, sheathing, etc. It should not be used on fine-finished lumber where a slightly raised grain would be objectionable. Intericide Copper Octoate 2% can be tinted to a stain like color with common universal paint colorants.

DIP TREATMENT: Lumber and small wooden structures should be totally immersed in Intericide Copper Octoate 2% treating solution for a period of from 30 seconds to 3 minutes depending on the thickness of the wood and the absorption required. Heavy lumber items should be dipped for 3 minutes, whereas light and absorptive stakes, window frames, etc. may be sufficiently treated in less time. The treated wood should be drained of excess solution and allowed to air dry. This usually takes 24 hours.

BRUSH COATING AND SPRAYING: Intericide Copper Octoate 2% is ideal for brushing or spraying all types of wood items as illustrated above. When using a brush or spraying, coverage should be complete or until runoff starts to occur. After permitting to dry for 24 hours, a second coat may be applied. Treated dried wood may be painted over if desirable.

CLEANING OF BRUSHES OR SPRAYING EQUIPMENT: Equipment and/or brushes may be cleaned under running water or in soap and water.