


If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


Henry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767)

Enclosure

Front Panel

INTERCIDE COPPER OCTOATE 2%
WOOD PRESERVATIVE-WATER DISPERSED

A Ready-to-Use Fungicide for the Control
of Mildew and Fungal Rot on Wood

Active Ingredient:

Copper 2-ethylhexanoate 11.02%
(Copper as metal--2%)

Inert Ingredients: 89.33%

Total 100.00%

Keep Out of Reach of Children

(12 pt)

CAUTION

(18 pt)

See Side Panel for Additional Precautionary Statements

EPA Reg. No. 34688-

EPA Est. No. 34688-NJ-1

Net Contents: 55 gals.

Interstab Chemicals, Inc.
500 Jersey Ave.--PO Box 638
New Brunswick, NJ 08903

ACCEPTED
with COMMENTS
in EPA Letter Dated:

NOV 25 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.
34688-28

Left Panel

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION

(18 pt)

Harmful if swallowed, inhaled or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment:


If in eyes, flush with plenty of water and get medical attention.

If swallowed, do not induce vomiting. Call a physician immediately.

If on skin, wash with plenty of soap and water.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.



Right Panel

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

(12 pt)

Do not contaminate water, food, or feed by storage or disposal.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Instructions for Treating Wood

Intericide Copper Octoate 2% is a ready-to use product containing Copper 2-ethylhexoate. It is a water containing system and can be used for treating lumber and heavy timbers such as fence posts, poles, structural timbers, stakes, sheathing, etc. It should not be used on fine-finished lumber where a slightly raised grain would be objectionable.

Dip Treatment: Lumber and small wooden structures should be totally immersed in Intericide Copper Octoate 2% treating solution for a period of from 30 seconds to 3 minutes depending on the thickness of the wood and the absorption required. Heavy lumber items should be dipped for 3 minutes, whereas light and absorptive stakes, window frames, etc. may be sufficiently treated in less time. The treated wood should be drained of excess solution and allowed to air dry. This usually takes 24 hours.

Brush Coating and Spraying: Intericide Copper Octoate 2% is ideal for brushing or spraying all types of wood items as illustrated above. When using a brush or spraying, coverage should be complete or until runoff starts to occur. After permitting to dry for 24 hours, a second coat may be applied.

Treated dried wood may be painted over if desirable.

Cleaning of Brushes or Spraying Equipment

Equipment and/or brushes may be cleaned under running water or in soap and water.

