


ACCEPTED

MAR 10 1994

Under the Federal Insecticide, Fungicide, and Rodenticide Act, registered for the pesticide use under No. 34688-69



SINESTO B

ACTIVE INGREDIENT

Alkyl* trimethylammonium chloride.....14.1%
(*Alkyl as in fatty acids of coconut oil)

INERT INGREDIENTS.....85.9%

TOTAL 100%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES

Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

IF ON SKIN

Immediately wash exposed skin with soap and water. Get prompt medical attention if irritation develops. Remove contaminated clothing, including shoes, and thoroughly clean and dry before reuse.

IF SWALLOWED

Do not induce vomiting. Drink plenty of water. Get immediate medical attention.

IF INHALED

Move to fresh air. Get immediate medical attention.

NOTE TO PHYSICIAN

Possible mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY
Akzo Chemicals Inc.
300 South Riverside Plaza
Chicago, Illinois 60606

EPA REGISTRATION NUMBER 34688-69
EPA ESTABLISHMENT NUMBER 34688-IL-1

NET VOLUME
55 gals. (208.2 liters)

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS
Danger. Corrosive. Causes severe eye and skin damage. Harmful or fatal if swallowed.

Do not get in eyes, on skin, or clothing. Avoid breathing vapor or mist. Wear chemical goggles, face shield, rubber gloves and impervious clothing when handling. Do not contaminate food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

PROHIBITIONS

Observe handling instructions given to prevent eye damage and skin burns. Do not contaminate water, food or feed by storage or disposal.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Plastic Containers: Triple rinse (or Equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Sinesto B is a concentrate of quaternary ammonium salts in water for use only at lumber mills as an anti-sapstain treatment on freshly cut lumber.

Sinesto B will prevent sapstain, mold and mildew stains (blue stain) during storage and transportation of lumber and its use is not intended or expected to extend to the use site. It is suitable for dilution with water and subsequent application on freshly cut lumber. Application of the dilute solution may be by dipping or spraying. The wood should be treated within 24 hours after cutting.

Wear rubber gloves or equivalent protection when handling solution and freshly treated lumber.

Sinesto B should be diluted with between 10 and 30 parts of water, by volume, depending on the severity of the stain problem. Avoid vigorous stirring to minimize foam formation. A board test is recommended in order to define the optimum dilution ratio. The contact time should be at least 30 seconds.

Treated wood should be held for 48 hours after treatment and must be protected against inclement weather. Dip tanks and drip aprons must be roofed, paved (or equivalent) and drained to prevent dilution and loss of the anti-sap stain solution. All equipment relative to the application of the sapstain should be properly maintained.

Treated sawdust and other wood wastes must be disposed of properly.

**FOR EMERGENCY HEALTH
INFORMATION CALL
(312) 906-7054**

34688-69
3/10/1994
121