

Scientific Water Treatment Chemicals & Equipment



BACTERIOSTAT AND ALGAECIDE FOR THE CONTROL OF MANY BIO-FOULING ORGANISMS OCCURING IN OPEN RECIRCULATING COOLING TOWERS

### Active Ingredient

Poly (Oxyethylene (Dimethyliminio) Ethylene ACCEPTED (Dimethyliminio) - Ethylene Dichloride ..... 94-/ Inert Ingredient: 

HELE REGISTER Weight of active ingredient per gallon . . . . . 1.29 pounds SUBJEC' SHED COMMENTS.

DIRECTIONS FOR USE: TOWERCIDE 722 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiologcial slime and other deposits. An initial slug of 4.0 to 10.0 fluid ounces of TOWERCIDE 722 to 1000 gallons of water, to provide a concentration of 32 to 80 parts per million TOWERCIDE 722 based on total weight of water in the system is recommended. Repeat until control is achieved. Subsequent slug additions of 1.0 to 10.0 fluid ounces of TOWERCIDE 722 per 1000 gallons of water (8 to 80 parts per million of TOWERCIDE 722) should be employed every two to five days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the microbiological problem. Consult your Dearborn Engineer. Slug additions should be made in the sum cooling towers.

WARNING CAUTION: KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed, inhaled or absorbed through skin. Avoid contact with skin and eyes. In case of eye contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

\*\*\*\*\*

Do not reuse empty drum. Rinse thoroughly with water and return to drum rece tioner or destroy. E. P. A. Reg. No. 3469

## **TOWERCIDE** 722

# 15.0%85.0%