

# CWB-4200

(anti-microbial)

## ACTIVE INGREDIENT

poly [oxyethylene (dimethyliminio) ethylene -  
[dimethyliminio] ethylene dichloride . . . . . 10%

INERT INGREDIENTS . . . . . 90%

Total 100%

This product contains 0.85 lb. of active ingredient  
per gallon and weighs 8.49 lbs. per gallon.

E.P.A. REG. NO. 34891-3



Contents: Liquid  
See Marking on Top of Drum  
For Net Weight

BEST DOCUMENT AVAILABLE

ACCEPTED  
34891-3  
JAN 16 1980  
UNDER THE FEDERAL PESTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
UNLESS OTHERWISE NOTED

## DIRECTIONS FOR USE GENERAL CLASSIFICATION

CWB-4200 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of CWB-4200, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.53 to 15.32 fluid ounces per 1000 gallons of water (12 to 120 parts per million of CWB-4200) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CWB-4200 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 24.7 to 41.2 fluid ounces of CWB-4200 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.9 to 41.2 fluid ounces per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

## KEEP OUT OF REACH OF CHILDREN WARNING

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinse that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.



Manufactured by

**Mitco Water  
Laboratories Inc.**

Post Office Box 1435 Winter Haven  
Florida 33880 Telephone 813-293-8536