

MICROBIOCIDES NO. 471

Active ingredients	17.5 percent
Disodium cyanodithioimidocarbonate	7.35 percent
Potassium N-methyldithiocarbamate	10.15 percent
Inert ingredients	82.5 percent
Weight per gallon	9.31 lb.
Weight of active ingredients per gallon	1.63 lb.

DIRECTIONS FOR USE

No. 471 is used to inhibit the growth of algae, bacteria, and fungi in recirculating commercial and industrial cooling water systems. Before treatment with No. 471 systems must be cleaned to remove algal growth, microbiological slime, and other deposits. Then the system should be treated with an initial slug addition of 3.3 to 6.6 fluid ounces of No. 471 per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 1.1 to 6.6 fluid ounces of No. 471 per 1,000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleedoff and the severity of the microbiological problem. Slug additions of No. 471 should be made to the sump of water cooling towers.

ACCOUNTED
17 1978
UN...
35909-3

WARNING

KEEP OUT OF REACH OF CHILDREN.

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label. Do not contaminate water by cleaning of equipment or disposal of wastes.

E.P.A. Reg. No. 35909-3
E.P.A. Establishment No.

Net Contents 5 Gallons

MANUFACTURED BY
Associated Water Conditioners, Inc. **NET LBS. 47**
Rt. 202, Mt. Kemble Avenue Morristown, N. J. 07960