MICROBIOCIDE NO. 473

	Percer	nt by weight
	Active ingredient	15.0 percent
-	Active ingredient	
	Inert ingredient	85.0 percent
	Weight per gallon	

APPLICATION

No. 473 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of No. 473 per 1000 gallons of water to provide a concentration of 4.8 to 12 parts per million of Active ingredient based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.0 to 10.0 fluid ounces of No. 473 per 1000 gallons of water (1.2 to 12 parts per million of Active ingredient) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION **KEEP OUT OF THE REACH OF CHILDREN**

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. If swallowed induce vomiting by giving 1 or 2 tablespoons of salt in warm water and sticking finger in back of throat. In case of contact with eyes flush with plenty of water for at least 15 minutes. If eye irritation persists call a physician. Avoid contamination of food.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on the label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

E.P.A. Reg. No. 35909-5 E.P.A. Establishment No. 35:09-NJ-1

> MANUFACTURED BY Associated Water Conditioners, Inc. Rt. 202, Mt. Kemble Avenue Morristown, N. J. 07960

Wt per gallon 3.58 pounds Net Contents