


If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee 
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

**SYSTEM 1
BACTERIOSTATIC
COUNTERTOP
WATER PROCESSOR
SY105-CT**

ACTIVE INGREDIENT: Silver (as elemental).....1.05%
INERT INGREDIENTS:.....98.95%

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

NOTE: After installation, run cold water 15 minutes to clear any loose carbon before drinking water.

REFER TO INSTRUCTIONS FOR PROPER USE.

DISPOSAL: Wrap filter in newspaper and discard in trash

For use on : 1/4 water line from municipally treated tap water in the home

MAXIMUM WATER PRESSURE.....85PSI
MAXIMUM FLOW RATE.....1 gallon per minute
MAXIMUM WATER TEMP.....85 degrees F

This unit has a capacity of up to 10,000 gallons. It is capable of treating 8 gallons of cold tap water daily for a period of 36 months. The useful life of this product is dependent on the quality of the water. If you notice a diminishing water flow, this indicates that the unit is nearing the end of its useful life.

EPA REGISTRATION NO.: 35920-
EPA ESTABLISHMENT NO: 35920-FL-1

**CLEAN WATER USA, INC
823 N.W. 57TH STREET
FT. LAUDERDALE, FL 33309
(305) 491-6611**

NET CONTENTS: One Bacteriostatic Water Filter Unit

ACCEPTED
WISCONSIN DEPT. OF REVENUE
MAY 22 1990
35920-8

ACCEPTED
with COMMENTS
in EPA Letter dated

MAY 22 1990

35920-8

INSTALLATION INSTRUCTIONS BACTERIOSTATIC WATER TREATMENT UNIT

Directions for Use

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS DEVICE IN A MANNER INCONSISTENT WITH ITS LABELING.

REFER TO THE LABEL FOR PROPER USE

Counter Top Model: ~~SK105-CT~~ SK105-CT

1. Open Box and lay out parts, 1 faucet diverter head, 2 adapter Rings, 2 Rubber washers.
2. Remove bubble screen from end of faucet.
3. Place diverter head on faucet to determine if an adapter ring is needed. If adapter ring is needed, check bag for ring and rubber washer and install them.
4. Attach the free end of the tubing to the water filter by pushing the hose on the hose barb in the unit.
5. Place unit in sink. Turn on the main faucet and divert water to the unit by pulling out the small button on the front of the diverter. When water flows from the unit, gently invert the unit to remove any remaining air, and let run for 5 to 10 minutes to flush out normal carbon dust.
6. Check all fittings for leaks.
7. Place the unit on the countertop in its service position and if necessary, cut the vinyl tubing to the appropriate length.

This unit is for use with COLD WATER ONLY. DO NOT run hot water through the unit.

The recommended flow rate for proper operation of this unit is ^{one} ~~one~~ gallons per minute. Excessive flow will diminish the units' effectiveness.