


APPLICATION

IRWIN POLY-QUAT 10 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of IRWIN POLY-QUAT 10 per 1000 gallons of water to provide a concentration of 5 to 10 parts per million of active ingredient based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.53 to 15.32 fluid ounces of IRWIN POLY-QUAT 10 per 1000 gallons of water (1 to 10 parts per million of active ingredient) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

ACCEPTED
35959-5
MAY 28 1976
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED



IRWIN ASSOCIATES INC

IRWIN

POLY-QUAT 10

ACTIVE INGREDIENT

Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio)-ethylene dichloride] 10.0%

INERT INGREDIENT 90.0%

Weight per gallon 8.49 pounds

Weight of active ingredient per gallon ... 0.85 pounds

NET CONTENTS: _____ EPA Reg. No. 35959-5

CAUTION EPA - EST. 35959-FI-1

KEEP OUT OF THE REACH OF CHILDREN

Irwin Associates, Inc.
Water Chemistry and Chemicals
P.O. Box 20636
St. Petersburg, Fla. 33742
Phone 813-522-0376 or Tampa 813-884-6265

KEEP OUT OF

Harmful if swallowed with skin. In case of at least 15 minutes. attention. Avoid co

This product is toxic effluent where it will Do not contaminate disposal of wastes.

Do not reuse empty or destroy by performing safe place away from