

# SCAB

ACTIVE INGREDIENTS.....0.75%  
disodium cyanodithioimidocarbonate.....(3.68%)  
potassium N-methyldithiocarbamate.....(5.07%)  
  
INERT INGREDIENTS.....91.25%  
  
Weight per gallon.....6.8 lbs.  
Weight of active ingredients per gallon......77lbs.

### APPLICATIONS

SCAB is used to inhibit the growth of algae, bacteria, and fungi in recirculating commercial and industrial cooling water systems. Before treatment with SCAB, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. Then the system should be treated with an initial slug addition of 6.9 to 13.9 fluid ounces of SCAB per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 2.3 to 13.9 fluid ounces of SCAB per 1,000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleedoff and the severity of the microbiological problems. Slug additions of SCAB should be made to the sump of the water cooling tower.

### WARNING

KEEP OUT OF REACH OF CHILDREN

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

### FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, give patient doses of powdered charcoal immediately, or all he can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

Do not reuse empty drum. Return to drum reconditioner.

### FISH AND/OR WILDLIFE CAUTIONS

This product is toxic to fish.  
Do not contaminate water by cleaning of equipment, or disposal of wastes.  
Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water.  
Apply this product only as specified on this label.

EPA Registration No.: 36511-  
EPA Establishment No.: 7701-PA-1  
NET WEIGHT 6.8 lbs.

Manufactured by:

ANCO, INC.

MEMPHIS, TENNESSEE

