



CAIS

# CAIS-cide B

Active ingredient.....  
Poly [oxethylene (dimethylimino) ethylene (dimethylimino)-  
ethylene dichloride].....1%. percent  
Inert ingredient.....98.0 percent

Weight per gallon.....8.58 pounds  
Weight of active ingredient per gallon.....1.2G pound

## APPLICATION

CAIS-cide B is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of CAIS-cide B per 1000 gallons of water to provide active ingredients 4.09 to 11.73 parts per million of CAIS-cide B based on the total weight of water in the system is recommended. Make an initial dosage until control is evident. Subsequent slug additions of 2 to 11.73 parts per million of CAIS-cide B should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological infestation. Slug additions should be made in the sump of water cooling towers.

## CAUTION KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. If swallowed induce vomiting by giving 1 or 2 tablespoons of salt in warm water and sticking finger in back of throat. In case of contact with eyes flush with plenty of water for at least 15 minutes. If eye irritation persists call a physician. Avoid contamination of food. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or puncturing and burying in a safe place.

This product is toxic to fish. Treated effluent should not be discharged where it will run off into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

MANUFACTURED BY

CENTRAL ARKANSAS INDUSTRIAL SERVICE INC.

CONWAY, ARK. 72032