

WOOD VAC—Penetrates all exterior and interior bare wood surfaces. Apply liberally with brush or spray on all wood, exterior and interior. The product is non-toxic and does not contain any harmful fumes or vapors. It is safe for use on all types of wood, including plywood, particle board, sash and sidings, stakes, tool sheds, fences, etc. A must for all plywood (protects against checking, over-prominent grain patterns showing thru stain; reduces grain raise and sanding necessary between primer and finish coat). **PAINFINDER**—Ideal foundation for Carroll Wood Glaze, paints, varnishes and enamels.

the end grain, so that it will penetrate deeply into the wood. Several coatings are better than one. Normally the wood should be seasoned dry before treating; however, applications on green or wet lumber will reduce its tendency to check, split and warp as it dries.

If lumber is intended to be in contact with the soil it should be immersed in Wood Vac for a minimum of 3 minutes or it should receive 2 or more flowing coats by brush or spray.

PREVIOUSLY FINISHED SURFACES—Remove all old coatings to permit proper penetration. Apply Wood-Vac on exposed surfaces and into all butt and lap joints, including the lines where old paints and wood meet. Wipe off excess Wood-Vac with a rag dampened with Carroll Paint Thinner. Allow wood to dry thoroughly (at least 24 hours) before applying Carroll Wood Glaze or other desired finishes. Where lacquers are used and rapid painting is necessary, a sealer coat may be applied after Wood-Vac treatment.

FOR SINGLE STAIN—Add 1 pint Tinting Color and 1 quart boiled linseed oil to 3 quarts of Wood-Vac. Stir the Tinting Color into a small quantity of Wood-Vac, then add the balance of Wood-Vac and linseed oil, stirring continuously.

WARNING

Vapor may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapor may concentrate and cause injury to plant or animal life.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this

CAUTION! COMBUSTIBLE CONTAINS PETROLEUM DISTILLATE AND PENTACHLOROPHENOL

Keep away from heat and open flame. If swallowed, induce vomiting by giving three teaspoonsful of table salt in a glass of warm water. Repeat until vomit is clear.

CALL PHYSICIAN. Never give anything by mouth to an unconscious person. Avoid contact with eyes, skin and clothing and breathing of vapor or spray mist. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly. Wear protective clothing and rubber gloves when handling freshly treated lumber. Close container after each use. Do not transfer contents to unlabeled bottles or other containers.

Use with adequate ventilation.



Retards W
Swell
Termi

WARNI
SWALI
SH
KEEP C
See addition

ONE GALLON • U. S. STANDARD

CARROLL/Ltd

CARROLL WOOD VAC

*Retards Warping
Swelling
Termites*

**WARNING! HARMFUL OR FATAL IF
SWALLOWED, VAPOR HARMFUL,
SKIN AND EYE IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
See additional precautions on side or back panel.**

CARROLL/Ltd., Inc. • Philadelphia 25, Pa.

ACCEPTED
36423-1
11-12-75
UNDER THE FEDERAL DEFENSE
PROCUREMENT AND CONSTRUCTION
ACT FOR ECONOMIC STABILIZATION
OF LABOR AND MATERIALS
CONTROL ACT OF 1975

FLAMMABLE! COMBUSTIBLE
PETROLEUM DISTILLATE
CONTAINS CHLOROPHENOL
Heat and open flame. If swallowed,
flush with water. Repeat until
relief is obtained. Do not induce
vomiting. If eye contact, flush
thoroughly with water. If skin
contact, wash with soap and water.
Wear protective clothing and rub-
ber gloves when handling freshly
treated lumber. Do not transfer
contents to unmarked bottles or
other containers. Use with
adequate ventilation.

NEW SURFACES—Apply liberally without dilution by brush or dipping, particularly on the end grain, so that it will penetrate deeply into the wood. Several coatings are better than one. Normally the wood should be seasoned dry before treating; however, applications on green or wet lumber will reduce its tendency to check, split and warp as it dries. If lumber is intended to be in contact with the soil it should be immersed in Wood Vac for a minimum of 3 minutes or it should receive 2 or more flowing coats by brush or spray.

PREVIOUSLY FINISHED SURFACES—Remove all old coatings to permit proper penetration. Apply Wood-Vac on exposed surfaces and into all butt and lap joints, including the lines where old paint and wood meet. Wipe off excess Wood-Vac with a rag dampened with Carroll Paint Thinner. Allow wood to dry thoroughly (at least 24 hours) before applying Carroll Wood Glaze or other desired finishes. Where lacquers are used and rapid painting is necessary, a sealer coat may be applied after Wood-Vac treatment.

WARNING

Vapor may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapor may concentrate and cause injury to plant or animal life. This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

EPA Establishment Reg. No. 36423-PA-01

**CAUTION! COMBUSTIBLE!
CONTAINS PETROLEUM
DISTILLATE AND
PENTACHLOROPHENOL**

Keep away from heat and open flame. If swallowed, induce vomiting by giving three teaspoonsful of table salt in a glass of warm water. Repeat until vomit is clear. CALL PHYSICIAN. Never give anything by mouth to an unconscious person. Avoid contact with eyes, skin and clothing and breathing of vapor or spray mist. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly. Wear protective clothing and rubber gloves when handling freshly treated lumber. Close container after each use. Do not transfer contents to unlabeled bottles or other containers.

Use with adequate ventilation.

WOOD VAC



**WARNING! HARMFUL OR FATAL IF
SWALLOWED, VAPOR HARMFUL,
SKIN AND EYE IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
See additional precautions on side or back panel.**

