



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY Washington, D.C. 20460

SEP 1 5 2008

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

Joanne K. Cashin Registration Compliance Advisor Arc Specialty Products P.O. Box 600 New Hampton, New York 10958

Subject:

Sterilizing Gas 4

EPA Registration 36736-4

Amendment Dated: June 16, 2008 EPA Received Date: June 17, 2008

Dear Joanne K. Cashin

The following amendment submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) as amended, is acceptable.

Proposed Amendment

Revised Label Adding Language for Ethylene Oxide

General Comments

A stamped copy of the accepted label is enclosed for your records. Submit (3) copies of your final printed label before distributing or selling the product bearing the revised labeling.

Should you have any questions or comments concerning this letter, please contact Velma Noble at (703)308-6233.

YMBOL Monager (31).

Product Manager (31).

Regulatory Management Branch1

Antimicrobial Division (7510c)

FA Form 1320-1A (1/90)

Printed on Recycled Parer

Sincerely

OFFICIAL FILE C

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! CAUSES EYE AND SKIN

BURNS. HARMFUL IF INHALED. MAY CAUSE NERVOUS SYSTEM DAMAGE.

DANGER! CANCER HAZARD AND REPRODUCTIVE HAZARD.

EFFECTS OF OVEREXPOSURE: May be fatal if inhaled in high concentrations. May cause irritation of the respiratory tract, chest tightness, headache, nausea, vomiting, diarrhea, light-headed feeling, dizziness, weakness, drowsiness, cyanosis, loss of coordination, convulsions, coma, delayed lung injury (fluid in the lungs), immediate or delayed skin irritation or blisters, allergic skin reaction. reaction. OTHER POSSIBLE DELAYED HEALTH EFFECTS:

May cause nervous system injury, cataracts, adverse reproductive effects, chromosomal and mutagenic changes, and cancer.

PEL: 1 PPM TWA (as per the Ethylene Oxide Standard 29 CFR 1910, 1047).

EL: 5 PPM - excursion limit 15 minutes.

ODOR: Ether-like at high concentrations. Exposure to toxic levels may occur without warning to or detection by the user.

PRECAUTIONS- Do not breathe vapor. Do not swallow. Do not get in eyes, on skin, or on clothing. Store and use with adequate ventilation in accordance with the Ethylene Oxide Standard (28 CFR

PERSONAL PROTECTION EQUIPMENT (PPE): A material that is chemical-resistant to this product is butyl rubber.

All handlers must wear at a minimum: Long-sleeved shirt and long plants. Shoes plus socks.

Chemical-resistant gloves, and

The employer shall provide a respirator that is adequate to protect the health, of the employee and ensure compliance with all other OSHA statutory and regulatory requirements (see 29 CFR 1910.1047 and 29 CFR 1910.134).

When handlers could have eye or skin contact with ETO or ETO

- Solutions, such as during maintenance and repair, vessel cleaning, or cleaning up spills, they must wear:
 Chemical-resistant attire, such as an apron, protective suit, or footwear that protects the area of the body that might contact ETO or ETO solutions, and
 face-sealing goggles, a full face shield, or a full-face
 - respirator.

- When wearing respirators:

 1. Follow the respirator manufacturer's user's instructions for changing canisters.
 - Respirators must be fit-tested and fit-checked using a program that conforms to OSHA's requirements (see 29CFR Part 1910.134).
 - Respirator users must be trained using a program that conforms to OSHA's requirements (see 29CFR Part 1910.134).

Respirator users must be examined by a qualified medical practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified medical practitioner is a physician or other licensed health care professional (PLHCP) physician or other licensed health care professional (PLHCP) who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. It does not need to be repeated unless the health status of respirator use conditions change (see 29CFR Part 1910.134).

Follow manufacturer's instructions for cleaning/maintaining PPE, If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.

Users should remove clothing/PPE immediately if pesticide gets Then wash thoroughly and put on clean clothing.

Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

PHYSICAL OR CHEMICAL HAZARDS: DANGERI - HIGHLY FLAMMABLE LIQUID AND GAS UNDER PRESSURE.

Contents under pressure. Do not use near flame, sparks, hot surfaces, or allow sources of ignition near the sterifization/furnigation

surfaces, or allow sources or ignition hear the sterilization/furnigation area. Sterilizing Gas 4 is extremely flammable and reactive. Ground all equipment (including this container) to prevent sparks.

LEAK - In case of leak evacuate area and keep personnel upwind, Shut off all sources of ignition. Use self-contained breathing apparatus and protective clothing, and shut off leak if without risk.

FIRE - In case of fire move container away from fire if without risk. Use water spray or fog nozzle to keep container cool.

FNUIRONMENTAL HAZARDS:

Do not discharge effluent containing this product into lakes, streams. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

It is imperative that users of this material be familiar with ARC Specialty Products' Material Safety Data Sheet for Sterilizing Gas 4, the label and valve tag attached to this cylinder.

STERI

STERILAN ACTIVE INGREDIEN

INERT INGREDIENT (CAS)

TOTAL:....

Keep Out of Re

DANGER

PRECAUTION AL USA no use este producto hast sido explicada ampliamen

Users must follow requiremen Exposure Standard for ethyle

FIRST AID

IN ALL CASES OF OVEREX ATTENTION IMMEDIATELY. DOCTOR OR EMERGENCY AT ONCE.

IF INHALED - Move person not breathing, call 911or respiration, preferably by mou difficult, give oxygen. Call a further treatment advice, ev under medical observation - :
IF ON SKIN OR CLOTHING shoes. Rinse skin immedia minutes. Call a poison contro Aerate, wash or clean conta goods.

SWALLOWED - Call immediately for treatment ad water if able to swallow. D anything by mouth to an unco IF IN EYES — Hold eye open for 15-20 minutes. Call a treatment advice

HOTLINE NUMBER - Have when calling a poison cor treatment. You may also co medical treatment information NOTE TO PHYSICIAN - Sk commonly result in skin irritat high concentrations, severe c respiratory tract may occur. I toms of systemic intoxications incoordination, and cardiac irr

Refer to ARC Specialty Produto locate MSDS for this produ Products at the telephone nui sent immediately.

801465 (Rev. 06/08 - supersedes 10/06)

ACCEPTED

SEP 1 5 2008

Under the Federal Insecticide, Fungicide, and Radentinise his as amended, for the cessitaregistres under EPA Reg. No.

isers must be examined by a qualified medical pensure physical ability to sately wear the style to be worn. A qualified medical practitioner is a other licensed health care professional (PLHCP) tuate the ability of a worker to wear a respirator, valuation consists of a questionnaire that asks at conditions (such as a heart, condition) that roblematic for respirator use. If concerns are neadditional evaluations, such as a physical to be necessary. The initial evaluation must be respirator use begins, it does not need to be less the health status of respirator use conditions. less the health status of respirator use conditions 29CFR Part 1910.134).

ir's instructions for cleaning/maintaining PPE, If s for washables exist, use detergent and hot sh PPE separately from other laundry.

hands before eating, drinking, chewing gum, sing the toilet.

love clothing/PPE immediately if pesticide gets

thiv and put on clean clothing.

ve PPE immediately after handling this product, of gloves before removing. As soon as possible, nd change into clean clothing.

EMICAL HAZARDS: ILY FLAMMABLE LIQUID AND GAS UNDER

ressure. Do not use near flame, sparks, hot ources of ignition near the sterifization/furnigation s 4 is extremely flammable and reactive. Ground ding this container) to prevent sparks.

teak evacuate area and keep personnel upwind, ces of ignition. Use self-contained breathing ctive clothing, and shut off leak if without risk, ite move container away from fire if without risk, fog nozzle to keep container cool.

HAZARDS:

ffluent containing this product into lakes, streams, or containing this product into taxes, streams, ceans or other waters unless in accordance with of a National Pollutant Discharge Elimination permit and the permitting authority has been prior to discharge of on not discharge effluent fluct to sewer systems without previously notifying treatment plant authority. For guidance contact oard or Regional Office of the EPA.

at users of this material be familiar with ARC Material Safety Data Sheet for Sterilizing Gas 4, tag attached to this cylinder.

STERILIZING GAS 4

STERILANT/FUMIGANT ACTIVE INGREDIENT, ETHYLENE ONIDE. .. 10% (CAS NO: 75-21-8)
INERT INGREDIENT, CARBON DIOXIDE.... 90% (CAS NO. 124-38-9)

Keep Out of Reach of Children

DANGER PELIGRO

PRECAUTION AL USARIO: Si usted no lee Ingles. no use este producto hasta que la etiqueta le haya sido explicada ampliamente.

Users must follow requirements of the OSHA Occupational Exposure Standard for ethylene oxide (29 CFR 1910.1047).

FIRST AID

IN ALL CASES OF OVEREXPOSURE GET MEDICAL ATTENTION IMMEDIATELY. TAKE PERSON TO A DOCTOR OR EMERGENCY TREATMENT FACILITY AT ONCE.

IF INHALED - Move person to fresh air. Keep warm. If person is not breathing, call 911or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. If breathing is difficult, give oxygen. Call a poison control center or doctor for further treatment advice, even if there are no symptoms. Keep under medical observation – symptoms may be delayed.

IF ON SKIN OR CLOTHING— Take off contaminated clothing and shoes. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Aerate, wash or clean contaminated clothing and discard leather goods.

IF SWALLOWED - Call poison control center or doctor immediately for treatment advice. Have person sip two glasses of water if able to swallow. Do not induce vemiting. Do not give

anything by mouth to an unconscious person.

IF IN EYES - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Call a poison control center or doctor for

treatment advice.

HOTLINE NUMBER — Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-424-9300 for emergency medical treatment information.

NOTE TO PHYSICIAN - Skin exposure to Sterilizing Gas 4 will commonly result in skin irritation with extensive blister formation. At high concentrations, severe conjunctivitis can occur. Irritation of the respiratory tract may occur, but without acute lung edema. Symptoms of systemic intoxication are headache, nausea, vomiting, incoordination, and cardiac irregularities, Treatment is symptomatic.

Refer to ARC Specialty Products' Sterilizing Gas 4 MSDS. If unable to locate MSDS for this product, please call ARC Specialty Products at the telephone number below and request that one be sent immediately.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a rinconsistent with its labeling. Employers in facilities that use ET comply with all of the requirements for ETO use specified in 2 1910.1047. This product may be used only in facilities that mequirements of the Ethylene Oxide Standard (28 CFR 1910 This product may be used only in non-portable (commercial) vac gas-tight chambers designed for use with 20% ethylene oxide carbon dioxide. This product may be used only by persons whoen trained in accordance with the Ethylene Oxide Standard (3 1910.1047). When used to starilize health care items, this product be used in non-portable (commercial) ethylene oxide gas starilize have FDA clearance.

In contract sterilization facilities, including facilities treating equipment and supplies, musical instruments, library/museum a cosmetics, and spices the following requirements must be follow

Sterilization/furnigation with ETO must be performed only in vac gas tight chambers designed for use with ETO.
Safety and awareness training is required for all employees ir office staff, information and training must be provided to all em in the facility at the time of initial assignment and annually the Thé safety training must include, at a minimum, the first most include. information

1. The most recent monitored ambient levels of ETO in the facility

2. The potential health effects from the levels of ETO in the facilit
3. The emergency response plan and how to respond in an eme
4. The availability of the Material Safety Data Sheet and other n
related to the health hazards of exposure to ETO.

In order to reduce ambient levels of ethylene oxide, length; aeration is encouraged. It can reduce potential long-term employees not directly involved in the ethylene oxide application

Air monitoring should included the entire facility including office break areas, and loading/unloading area

1. AS A STERILANT AND FUMIGANT GAS:

A. For complete use directions (including type of surfaces, ob items/products recommended for treatment, pre-cleaning inst concentration of gas per unit volume of closed space to be exposure time/temperature, relative humidity, ventilation/aerati and method of monitoring to be used) refer to the ethylene of sterilizer manufacturers' Operators Manuals.

This product may be used only to sterilize medical or laborator pharmaceuticals, and aseptic packaging, (see 21 CFR 201.1(c) to reduce microbial load on cosmetics, whole and ground so other seasoning materials (see 40 CFR 180.151), and archival material or library objects.

USE THIS PRODUCT WITHIN 120 DAYS OF ITS PURCHASE. DO NOT REMOVE THIS LABEL

In case of accident or emergency call CHEMTREC at 1-800-424-9300.

> Distributed By: **ARC Specialty Products Balchem Corporation** P.O. Box 600 · New Hampton, NY 10958 Tel: 845-328-5611 Fax: 845-326-5706 www.arcspecialtyproducts.com

ACCEPTED

SEP 1 5 2008

Under the Federal Insecticide, Fungicide, and Rodenticade Aut as amended, for the ්දැල්පොළා ගක්ෂ EPARsy No 767

IZING

JMIGANT DYLENE OXIDE. .. 10% 5-21-81 ION DIOXIDE... 90% 4-38-91

.... 100° •

h of Children

PELIGRO

Si usted no lee Ingles. : la ctiqueta le haya

the OSHA Occupational ide (29 CFR 1910,1047).

JRE GET MEDICAL E PERSON TO A ATMENT FACILITY

esh air. Keep warm. If person is ambulance, then give artificial mouth, if possible. If breathing is

ion control center or doctor for there are no symptoms. Keep oms may be delayed. te off contaminated clothing and with plenty of water for 15-20 er or doctor for treatment advice. ted clothing and discard leather

on control center or doctor Have person sip two glasses of induce vamiting. Do not give us person.

inse slowly and gently with water n control center or doctor for

oduct container or label with you enter or doctor, or going for 1-800-424-9300 for emergency

posure to Sterilizing Gas 4 will ith extensive blister formation. At ctivitis can occur. Irritation of the ithout acute lung edema. Symp-headache, nausea, vomiting, rities, Treatment is symptomatic.

iterilizing Gas 4 MSDS. If unable tase call ARC Specialty below and request that one be

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Employers in facilities that use ETO must comply with all of the requirements for ETO use specified in 29 CFR 1910.1047. This product may be used only in facilities that meet the requirements of the Ethylene Oxide Standard (29 CFR 1910.1047). This product may be used only in non-portable (commercial) vacuum or gas-tight chambers designed for use with 20% ethylene oxide. 80% carbon dioxide. This product may be used only by persons who have been trained in accordance with the Ethylene Oxide Standard (29 CFR 1910.1047). When used to sterilize health care items, this product must be used in non-portable (commercial) ethylene oxide gas sterilizers that have FDA clearance.

In contract sterilization facilities, including facilities treating medical equipment and supplies, musical instruments, library/museum artifacts, cosmetics, and spices the following requirements must be followed:

Sterilization/furnigation with ETO must be performed only in vacuum or gas tight chambers designed for use with ETO.
Safety and awareness training is required for all employees including office staff. Information and training must be provided to all employees in the facility at the time of initial assignment and annually thereafter. The safety training must include, at a minimum, the following

- 1. The most recent monitored ambient levels of ETO in the facility;
- The potential health effects rom the levels of ETO in the facility; The emergency response plan and how to respond in an emergency:
- The availability of the Material Safety Data Sheet and other materials related to the health hazards of exposure to ETO.

In order to reduce ambient levels of ethylene oxide, lengthy facility aeration is encouraged. It can reduce potential long-term risks to employees not directly involved in the ethylene oxide applications.

Air-monitoring should included the entire facility including office space, break areas, and loading/unloading areas

AS A STERILANT AND FUMIGANT GAS:

A. For complete use directions (including type of surfaces, objects, or items/products recommended for treatment, pre-cleaning instructions, concentration of gas per unit volume of closed space to be treated, exposure time/temperature, relative humidity, ventilation/aeration time. and method of monitoring to be used) refer to the ethylene oxide gas sterilizer manufacturers Operators Manuals.

This product may be used only to sterilize medical or laboratory items, pharmaceuticals, and aseptic packaging, (see 21 CFR 201.1(d)(5)), or to reduce microbial load on cosmetics, whole and ground spices or other seasoning materials (see 40 CFR 180.151), and artifacts, archival material or library objects.

USE THIS PRODUCT WITHIN 120 DAYS OF ITS PURCHASE. DO NOT REMOVE THIS LABEL

In case of accident or emergency call CHEMTREC at 1-800-424-9300.

> Distributed By: **ARC Specialty Products Balchem Corporation** P.O. Box 600 · New Hampton, NY 10958 Tel: 845-326-5611 Fax: 845-326-5706 www.arcspecialtyproducts.com

Net Contents:

lbs

This product may not be used on or in any form of basil.

After August 1, 2008, this product may only be applied to or on spices, dried vegetables or seasonings utilizing an ETO sterilization method that uses a single sterilization chamber to pre-condition and aerate with an alternating vacuum and aeration purging procedure. If you wish to employ an alternative method to that described below, you must contact the Environmental Protection Agency Office of Pesticide Programs for instruction on how to receive authorization.

Place spices in the treatment chamber. Assure that the mixture of ethylene oxide and air is compatible with the chamber design, then, introduce into the chamber a concentration of Ethylene Oxide not to exceed 500 mg/L, with a dwell time not to exceed 6 hours. Then evacuate the gas from the chamber using a sequence of not less than 21 steam washes (injections and evacuations) between 1.5 PSIA (27" Hg) and 5.0 PSIA (20"Hg) while maintaining a minimum chamber temperature of 115° F.

- B. Sterilization/furnigation with Sterilizing Gas 4 must be performed only in vacuum or gas tight chambers designed for use with Sterilizing
- only in vacuum or gas tight chambers designed for use with Sterilizing Gas 4.

 C. Sterilizing Gas 4 cycle parameters depend on several sterilizing/furnigating variable factors: pre-conditioning (if any); exposure time; chamber air pressure; gas concentration; types and quantities of items to be sterilized/furnigated; packaging; load configuration in the chamber; microbial challenge method; desired degree of disinfection; and the desired performance of the sterilization/furnigation cycle parameters should be those prescribed by the equipment manufacturer. If other cycle parameters are used, the safety and efficacy of the alternate cycle parameters use a validated and are the responsibility of the user. NEVER USE PARAMETERS WHICH ALLOW FLAMMABLE MIXTURES OF STERILIZING GAS 4 AND AIR TO ENTER THE CHAMBER.
- 2. INSTALLATION AND OPERATION OF THE CONTAINER Follow the directions on the valve tag attached to this container.

STORAGE AND DISPOSAL

Do not contaminate food, feed, or water by storage and disposal.

PESTICIDE STORAGE Use in accordance with tag attached to valve.

Store in cool, well-ventilated area. Avoid exposure to heat or direct sunlight as may cause polymerization.

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous.

Improper disposal of excess pesticide, spray, or mixture of rinsate is a Improper disposal of excess pessicios, spray, or instant of initiate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL When empty, return to supplier only. Before returning container to supplier:

- Cylinder pressure should be below 600 psig when empty. Check that container valve is closed.
- Replace valve plug tightly in valve outlet.
- Check container valve and plug for leaks prior to shipment.

EPA Registration No. 36736-4 EPA Establishment No. 35084-PA-2 36736-SC-01 36736-SC-01 36736-MO-01 36736-NY-01