

PM 31

36736-8

2-23-99

1043

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB 23 1999

ARC Chemical Division
Balchem Corporation
P.O. Box 180
Slate Hill, NV 10973

Subject: Ethylene Oxide - MUP
EPA Registration No. 36736-8
Your Amendment Dated: 11/23/98

Attention: Ms. Diane Powers,
VP of Registration

The amendment referenced above submitted in connection with registration under FIFRA, as amended, for a revised, updated label is acceptable provided the following issues are addressed before you release the product for shipment.

1. According to the Label Review Manual (2nd Edition), Chapter 6, the ingredient statement should be revised to reflect the following:

Active Ingredient: Ethylene Oxide 100.0 %

The CAS Registry number is not necessary.

2. Under the "Statements of Practical Treatment", the following sentence, "If breathing is difficult, give oxygen," should be added to the "IF INHALED" section, preferably after the second sentence.
3. The EPA registration number should be revised to reflect 36736-8 instead of 36736-1.

A stamped copy of the label is enclosed for your records. Please submit one (1) copy of the final printed label prior to the release of the product for shipment.

If you have any questions regarding this letter please contact Jacqueline Campbell at (703) 308-6416.

CONCURRENCES

SYMBOL	7510C							
SURNAME	Campbell							
DATE	2/23/99							

EPA Form 1320-1A (1/90)

Printed on Recycled Paper

OFFICIAL FILE COPY

Sincerely,



Velma Noble
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510C)

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! CAUSES EYE AND SKIN BURNS. HARMFUL IF INHALED. MAY CAUSE NERVOUS SYSTEM DAMAGE.

DANGER! CANCER HAZARD AND REPRODUCTIVE HAZARD.

EFFECTS OF OVEREXPOSURE: May be fatal if inhaled in high concentrations. May cause irritation of the respiratory tract, chest tightness, headache, nausea, vomiting, diarrhea, light-headed feeling, dizziness, weakness, drowsiness, cyanosis, loss of coordination, convulsions, coma, delayed lung injury (fluid in the lungs), immediate or delayed skin irritation or blisters, allergic skin reaction.

OTHER POSSIBLE DELAYED HEALTH EFFECTS: May cause nervous system injury, cataracts, adverse reproductive effects, chromosomal and mutagenic changes, and cancer.

- PEL: 1 PPM TWA (as per the Ethylene Oxide Standard 29CFR1910.1047).
EL: 5 PPM - excursion limit 15 minutes
ODOR: Ether-like at high concentrations. Exposure to toxic levels may occur without warning to or detection by the user.

PRECAUTIONS - Do not breathe vapor. Do not swallow. Do not get in eyes, on skin, or on clothing. Store and use with adequate ventilation in accordance with the Ethylene Oxide Standard (29 CFR1910.1047).

PHYSICAL OR CHEMICAL HAZARDS: DANGER! - HIGHLY FLAMMABLE LIQUID AND GAS UNDER PRESSURE.

Contents under pressure. Do not use near flame, sparks, hot surfaces, or allow sources of ignition near the sterilization/fumigation area. Ethylene Oxide is extremely flammable and reactive. Ground all equipment (including this container) to prevent sparks.

LEAK - In case of leak evacuate area and keep personnel upwind. Shut off all sources of ignition. Use self-contained breathing apparatus and protective clothing, and shut off leak if without risk.

FIRE - In case of fire move container away from fire if without risk. Use water spray or fog nozzle to keep container cool.

ENVIRONMENTAL HAZARDS:

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Effluent System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

It is imperative that users of this material be familiar with ARC Specialty Products' Material Safety Data Sheet for 100% Ethylene Oxide, the label and valve tag attached to this drum.

ETHYLENE OXIDE - MUP

FOR MANUFACTURING USE

ACTIVE INGREDIENT ETHYLENE OXIDE 100% BY WEIGHT

CAS REGISTRY NUMBER 75-21-8

KEEP OUT OF REACH OF CHILDREN

DANGER PELIGRO

PRECAUTION AL USARIO: Si usted no lee ingles, no use este producto hasta que la etiqueta le haya sido explicada ampliamente.

Users must follow requirements of the OSHA Occupational Exposure Standard for ethylene oxide (29CFR1910.1047).

STATEMENT OF PRACTICAL TREATMENT

IN ALL CASES OF OVEREXPOSURE GET MEDICAL ATTENTION IMMEDIATELY. TAKE PERSON TO A DOCTOR OR EMERGENCY TREATMENT FACILITY AT ONCE.

IF INHALED - Remove exposed person to fresh air. Keep warm. If breathing has stopped, administer artificial respiration or oxygen. Do not give anything by mouth to an unconscious person. Call a physician even if no symptoms are present. Keep under medical observation. Symptoms may be delayed.

IF ON SKIN - Immediately remove contaminated clothing and shoes. Wash contaminated area thoroughly with soap and water. Call a physician. Aerate, wash or clean contaminated clothing and discard leather goods.

IF SWALLOWED - Give at least two glasses of water. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Call a physician.

IF IN EYES - Hold eyelid open and flush with a steady, gentle stream of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN - Skin exposure to Ethylene Oxide will commonly result in skin irritation with extensive blister formation. At high concentrations, severe conjunctivitis can occur. Irritation of the respiratory tract may occur, but without acute lung edema. Symptoms of systemic intoxication are headache, nausea, vomiting, incoordination, and cardiac irregularities. Treatment is symptomatic. Refer to ARC Specialty Products' Ethylene Oxide MSDS. If unable to locate MSDS for this product, please call ARC Specialty Products at the telephone number below and request that one be sent immediately.

- Net Contents: 400 lb. []
175 lb. []
20 lb. []

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. It is the employer's responsibility to follow the requirements of the Ethylene Oxide Standard (29CFR1910.1047).

This product may be used only in facilities that meet the requirements of the Ethylene Oxide Standard (29 CFR 1910.1047). This product may be used only according to its EPA-registered instructions for use. This product may be used only by persons who have been trained in accordance with the Ethylene Oxide Standard (29 CFR 1910.1047). When used to sterilize health care items, this product must be used in ethylene oxide gas sterilizers that are approved by the registrant of the sterilant and listed in the current EPA-registered and/or FDA-approved instructions for use.

1. FOR USE IN THE FORMULATION OF STERILIZING GAS MIXTURES:

This product may be used for formulation into a sterilant/fumigant for the following pesticidal uses: to sterilize medical or laboratory items, pharmaceuticals and aseptic packaging, (see 21 CFR 201.1(4d)) or as fumigant to reduce microbial load on cosmetics, whole and ground spices or other seasoning materials, (see 40 CFR 180.151 and 40 CFR 185.2850), and artifacts, archival material or library objects.

A. This product may be mixed with carbon dioxide, hydrochlorofluorocarbon material, or chlorofluorocarbon material, as an inerting substance to reduce flammability.

B. The amount of Ethylene Oxide used to formulate the blended product shall be an amount sufficient to equal the percent of the active ingredient in the formulators' product as registered with the United States Environmental Protection Agency (i.e. - in a registered product containing 10% ethylene oxide and 90% inerting gas in a 100 lb. container, fill container with 10 lbs. ethylene oxide and 90 lbs. inerting substance).

2. INSTALLATION AND OPERATION OF THE CONTAINER - Follow the directions on the valve tag attached to this container.

STORAGE & DISPOSAL

Use in accordance with tag attached to valve. Store in cool, well ventilated area. Avoid exposure to heat or direct sunlight as may cause polymerization. When empty, return to supplier only. Before returning container to supplier:

- 1. Pressurize container with nitrogen to 50 psig total pressure at 70 degrees F.
2. Replace valve plugs tightly in valve outlets.
3. Check container valve and plugs for leaks prior to shipment.

USE THIS PRODUCT WITHIN 120 DAYS OF ITS PURCHASE.

ACCEPTED with COMMENTS in EPA Letter Dated: EPA Registration No. 36736-1 EPA Establishment No. [] 36736-M-01 [] 36736-9C-01

Distributed By: 2/23/99
ARC Specialty Products, Federal Insecticide, Fungicide, and Rodenticide Act
Balchem Corporation, 10075
P.O. Box 180 - Slate Hill, NY 10978
Tel: 914-355-5344 Registered under EPA Reg. No.
Fax: 914-355-7619

In case of accident or emergency, call CHEMTREC at 800-424-9300. 36736-8

DO NOT REMOVE THIS LABEL.