3

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

[illegible]

[illegible] empty [illegible] container [illegible] bury

[illegible] for recycling [illegible] or disposal [illegible] at a safe place. For [illegible] that cannot be used or recycled [illegible] disposed of in a landfill approved for [illegible] or burned in a safe place away [illegible] Open burning is prohibited.

MFG. BY B & M INTERNATIONAL
THIBODAUX, LA. 70301

EPA REG. NO. 36999-35 EPA EST. NO 36999 LA 1

NET CONTENT 1 GALLON (3.8 L.)

ACCEPTED
36999-35
OCT 3 1979

UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR [illegible] REGISTRATION NO.

# G800-L

## A BROAD SPECTRUM MICROBICIDE FOR USE IN RECIRCULATING WATER SYSTEMS

| | |
|---|---|
| ACTIVE INGREDIENT | |
| Poly oxyethylene (dimethylimino) ethylene (dimethylimino) ethylene dichloride | 10.0 |
| INERT INGREDIENT | 90.0 |
| TOTAL | 100.0 |

This product contains 0.85 [illegible] and weighs 8.49 lb per gallon.

CAUTION KEEP OUT OF REACH OF CHILDREN

HARMFUL IF SWALLOWED AVOID BREATHING VAPORS
AVOID CONTACT WITH SKIN, EYES, AND CLOTHING

See additional precautions and first aid statement on left side panel

## DIRECTIONS FOR USE

### GENERAL CLASSIFICATION

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

G800-L is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to dosing, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of G800-L per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of G800-L, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.53 to 15.32 fluid ounces of G800-L per 1000 gallons of water (12-20 parts per million of G800-L) should be employed 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug addition should be made in the sump of water cooling towers.

G800-L is used to control bacteria in industrial air washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 24.7 to 41.2 fluid ounces of G800-L per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.9 to 41.2 fluid ounces of G800-L per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleed-off and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the air wash system.

[illegible] DOMESTIC ANIMALS

MFG. BY B & M INTERNATIONAL
THIBODAUX, LA. 70301

EPA REG. NO. 36999-35 EPA EST. NO. 36999-LA-1

NET CONTENT 1 GALLON (3.8 L.)

ACCEPTED
36999-35
OCT 3 1979
UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR TEMPORARY DIVISION REGISTRATION NO.

# G800-L

A BROAD SPECTRUM MICROBICIDE
FOR USE IN RECIRCULATING WATER SYSTEMS

[illegible]

CAUTION: KEEP OUT OF REACH OF CHILDREN

HARMFUL IF SWALLOWED. AVOID BREATHING VAPORS
AVOID CONTACT WITH SKIN, EYES AND CLOTHING

For additional precautionary and first aid statements see left side panel

DIRECTIONS FOR USE
GENERAL CLASSIFICATION
IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

G800 L [illegible] deposits. A[illegible] G800 L [illegible] provide a [illegible] 8 to 120 [illegible] For of G800 L [illegible] this system, [illegible] control [illegible]

Subsequent slug additions of 1.53 to 16.3[illegible] ounces of G800 L per 1000 gallons of water [illegible] 20 parts per million of G800 L [illegible] 2 to 5 days, as needed. The [illegible] depends upon the [illegible] amount of bleed-off [illegible] severity of the microbiological problem. Slug additions should be made to the sump of water cooling towers.

G800 L is used to control bacteria in industrial washing systems that [illegible] effective most [illegible] rating components. Prior to using system should be cleaned to remove bacterial [illegible] and other deposits. An initial slug dose of 24.7 to 41.2 fluid ounces of G800 L per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.9 to 41.2 fluid ounces of G800 L per 1000 gallons of water should be employed each 1 to 5 days, as needed. The frequency of addition depends upon the relative amount of bleed-off and severity of the biological problem. Slug additions may be made to the sump or to the water collection tray of the wash system.

BEST DOCUMENT AVAILABLE