# ETHY-GEN® II

# **CONCENTRATE**

ONLY FOR USE WITH A CATALYTIC GENERATOR TO PRODUCE ETHYLENE TO ACCELERATE RIPENING OF:

Avocados, Bananas, Citrus Fruit, Melons, Papayas, Pears, Tomatoes and Tobacco

2 days 1 committees and 1 country	
ACTIVE INGREDIENT	
Ethanol	.88%
INERT INGREDIENTS6	.12%
TOTAL 100	.00%

# WARNING

KEEP OUT OF REACH OF CHILDREN
NOT INTENDED FOR
HUMAN CONSUMPTION
FLAMMABLE
KEEP AWAY FROM HEAT AND FLAME

## STATEMENT OF PRACTICAL TREATMENT

If Swallowed: Induce vomiting by touching the back of the throat with finger or blunt object. Get medical attention immediately.

If Inhaled: Remove from exposure and get medical attention immediately.


If in Eyes: Flush with water for at least 15 minutes. Get medical attention immediately.

If on Skin: Irrigate immediately with water.
See Side panel for additional Precautionary Statements.

#### Mfg. By CATALYTIC GENERATORS, INC.

1185 Pineridge Road Norfolk, VA 23502 (804) 855-0191

Establishment No. 37433-VA-1 E.P.A. Reg. No. 37433-1 Net Contents --- 64 Ounces --- Two (2) U.S. Quarts



### FLAMMABLE

Keep away from heat and flame.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. STORAGE-Store in dry locked storage area, at temperatures below 125 F.

CONTAINER DISPOSAL-Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by stage and local authorities, by burning. If burned, stay out of sanke.

#### **DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Avocados, Bananas, Citrus Fruit, Melons, Papayas, Pears and Tomatoes.

Use in a Catalytic Generator the first 24 hours of ripening period. One (1) quart used as directed in 4,000 to 10,000 cubic feet ripening room produces ethylene concentrations varying from 4 to 1,200 P.P.M. over a period of 12-48 hours. One (1) pint used as directed in 1,000 to 6,000 cubic feet ripening room produces ethylene concentrations varying from 5 to 500 P.P.M. over a period of 6-24 hours.

### **TOBACCO (FLUE-CURED)**

Use in a Catalytic Generator immediately after filling curing system. Two (2) quarts used as directed in 1.500 to 2,500 cubic feet curing system produces ethylene concentrations varying from 15 to 300 P.P.M. over a period of 12-24 hours. Use additional two (2) quarts of ETHY-GEN<sup>k</sup> or ETHY-GEN<sup>k</sup> II as required.

#### **USE PRECAUTIONS**

Anyone using this product in any other type curing system or room size should contact us prior to use. The ripening room or curing system should be reasonably air-tight, all vents and doors closed, cracks or holes in walls and doors should be repaired or covered over.

#### WARRANTY

Seller's liability for breach of warranty, express or implied, in connection with the sale or lease of this product shall be limited to repairs or replacement at seller's expense of the defective product, and in no case shall seller be liable for incidental or consequential damages.

#### **IMPORTANT NOTICE**

Use of any other product other than ETHY-GEN<sup>a</sup> or ETHY-GEN<sup>a</sup> II CONCENTRATE may damage the catalytic generator supplied by Catalytic Generators, Inc. Also, use of other products in the generator may produce harmful by-products.