


G-100W



ACTIVE INGREDIENT

Potassium dimethyldithiocarbamate 20.0%

INERT INGREDIENTS

80.0%

This product contains 2.26 lb. of active ingredient per gallon and weighs 11.31 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN
WARNING**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

WARNING: Causes eye damage and skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: *In case of skin contact*, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. *If product gets in the eyes*, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. *If product is swallowed*, call a physician immediately. If patient is conscious, induce vomiting by stroking or tickling the patient's throat or far back on patient's tongue. Emetics such as 2 teaspoonsful (10 mL) of ipecac syrup or 1 teaspoonful (5 mL) of dry mustard in warm water to form a paste or even so in warm water can be used. Repeat until vomit fluid is clear. Then have patient drink plenty of milk, gelatin solution, beaten egg whites, flour and water, or other nonoily demulcent. *Never induce vomiting or give anything by mouth to an unconscious person.*

Note to physician. Probable mucosal damage may contraindicate gastric lavage.
ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

**DIRECTIONS FOR USE
GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

G-100W is used in cooling water systems and industrial air washing systems to control microbiological slime. In cooling systems, add 2.9 to 8.6 fl. oz. of G-100W per 1000 gal. of water to the cooling tower sump. In air washing systems, add 10 to 17.2 fl. oz. of G-100W per 1000 gal. of water to water collection trays. Repeat treatments every 1-5 days or as needed. The required frequency depends on relative amount of bleed and severity of slime problem.

G-100W is used to control sulfate reducing bacteria in petroleum secondary recovery waterflooding operations at dosages of 2.38 to 4.76 fl. oz. of G-100W per 1000 gal. of water treated. Technical assistance in applying G-100W to a particular secondary recovery system is available upon request when a description of the problem is provided.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides, or buried in a safe place away from water supplies.

CONTAINER DISPOSAL:

METAL: Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place. Containers over 30 gallons should be resealed before offering for reconditioning.

PLASTIC: Containers under 30 gallons must not be reused but should be triple rinsed and disposed of in an incinerator or landfill approved for pesticide containers or buried in a safe place. Containers over 30 gallons are to be resealed and offered for reconditioning or triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place.

GENERAL: Consult Federal, State, or Local disposal authorities for approved alternative procedures.

Manufactured by

Dresser Industries, Inc.

Magcobar Group, Magcobar North America Division

P. O. Box 6504, Houston, TX 77005

EPA REG NO 38097 11

EPA EST NO.

NET CONTENTS