

WARCO ALGAECIDE-60
MANUFACTURED BY WARREN COOK CHEMICALS, INC.
OAK & ASTOR STS. MONEE, ILLINOIS 60449

COMPOSITION

Active ingredient.....Percent by weight
60.0 percent

Poly (oxyethylene (dimethyliminio)
ethylene (dimethyliminio)- ethylene
dichloride) 60 percent

Inert ingredient 40 percent

Weight per gallon..... 9.6 pounds

Weight of active ingredient
per gallon 7.56 pounds

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

APPLICATION

WARCO ALGAECIDE-60 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 0.9 to 2.2 fluid ounces of WARCO ALGAECIDE-60 per 1000 gallons of water to provide a concentration of 8 to 20 parts per million of WARCO ALGAECIDE-60 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.2 to 2.2 fluid ounces of WARCO ALGAECIDE-60 per 1000 gallons of water (2 to 20 parts per million of WARCO ALGAECIDE-60) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the pump of water cooling towers.

EPA Reg. No. 26488-2

UNITED STATES
DEPARTMENT OF AGRICULTURE
NATIONAL AGRICULTURAL
LIBRARY
WASHINGTON, D.C. 20540

