


# BESST 305-S



## INDUSTRIAL WATER <sup>Microbiocide</sup> BIOCIDES

### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

#### DANGER:

Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

#### ENVIRONMENTAL HAZARDS:

This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your regional office of EPA.

#### PHYSICAL AND CHEMICAL HAZARDS:

Strong oxidizing agent. Mix only with water. Use clean utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals may start a chemical reaction with generation of heat, generation of

hazardous gases and possible generation of fire explosion. In case of contamination or decomposition do not reseal container. If possible isolate container in open air or well ventilated area. Flood with large volume of water if necessary.

#### Active Ingredients:

Sodium Dichloro-s-triazinetrione 99.3%

Inert Ingredients: 0.7%

Provides 55% available chlorine

EPA Reg. No. 225-225 (EPA Est. No. 39118-PA-1)

**KEEP OUT OF REACH  
OF CHILDREN  
DANGER**

#### PRACTICAL TREATMENT: FIRST AID

If swallowed feed bread soaked in milk followed by olive oil or cooking oil. Call a physician immediately.

If on skin: Brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists get medical attention.

If in eyes: Flush with cold water for at least 15 minutes. Get medical attention.

SEE ADDITIONAL PRECAUTIONS ON SIDE PANEL.

## Net Contents

BESST 305-S Industrial water <sup>Microbiocide</sup> biocide is recommended for use in either industrial cooling water or in industrial water for washing air.

#### DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

#### Industrial Cooling Tower Water

For badly fouled systems add 1% or 3 lbs. of BESST 305-S Industrial water <sup>Microbiocide</sup> biocide daily for each 10,000 gallons of system water. This provides 10 ppm and 20 ppm available chlorine respectively. Repeat each day until the system is free of visible fungi and algal slime. This condition is usually indicated when a free available chlorine residual of at least 1 ppm is found four hours after the treatment. When a system is under control add 5 or 10 oz. of BESST 305-S industrial water <sup>Microbiocide</sup> biocide daily per 10,000 gallons of system water to provide 2 or 4 ppm free available chlorine respectively. These amounts may be raised or lowered as required and indicated by water conditions and by test for chlorine residual. Reliable test kits for testing free available chlorine are available and should be used. The BESST 305-S industrial water <sup>Microbiocide</sup> biocide should be added

directly from the container to a place in the system where it will be evenly mixed with the water.

#### Water for Air Washers

In starting up a new system add ¼ lb. to ½ lb. of BESST 305-S Industrial water <sup>Microbiocide</sup> biocide per 10,000 gallons of water in the system. This provides 4 or 5 ppm of free available chlorine respectively. For routine control add 1% to 2% oz. of BESST 305-S industrial water biocide per 10,000 gallons of water daily. This will provide 0.5 or 1.0 ppm free available chlorine. These amounts may be raised or lowered as required and indicated by water conditions and tests for free available chlorine. Reliable test kits are available for testing chlorine and should be used.

#### Storage and Disposal

Keep product dry in tightly closed container when not in use. Store in a cool, dry well-ventilated area away from heat or open flame. In case of decomposition isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area or bury in a safe place.

**ONLY FOR SALE TO, USE OR  
STORAGE BY SERVICE PERSONS**

## BESST CHEMICALS INC.

P.O. Box 4112  
Bayamón Gardens Station  
Bayamón, P.R. 00620