

JUN 1 1 1981

Under the Federal Insecticide. Fungicide, and Rodenticide Act, as amended, for the pesticide

ALGAECIDE

QUALITY AND SERVICE YOU CAN DEPEND ON

ACTIVE INGREDIENT Poly [oxyethylene (dimethyliminio) ethylene-(dimethyliminio) ethylane dichloride) 15.0% INERT INGREDIENT 85.0% This product contains 1.29 lb. of active ingredient per gallon and weighs 8.58 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swellowed, drink promptly a large quantity of milk, egg whites, galatic solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams or odnos Permits may be required for discharge containing this posticide into lakes, streams, ponds or public we or guidance, contact the regional office of the Environ mental protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner. inconsistent with its labeling.

AQUA TREAT A-106 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of AQUA TREAT A-106 per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of AQUA TREAT A-106, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.0 to 10.0 fluid ounces of AQUA TREAT A-106 per 1000 gallons of water (8 to 80 parts per million of AQUA TREAT A-106) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

AQUA TREAT A-106 is used to control bacteria in industrial airwashing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 14.8 to 24.7 fluid ounces of AQUA TREAT A-106 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 10.1 to 24.7 fluid ounces of AQUA TREAT A-106 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivelent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

> Manufactured by: Aqua Treat Chemicals, Inc. 1166 87th Street • Daly City, CA 94105 (415) 992-2991

EPA REG. NO. 39327-17 EPA EST. NO.

NET CONTENTS: _

17