

CAUTION

**CONTAINS METHYL
ISOBUTYL KETONE
AND CUPROUS OXIDE**

**DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME.**

Avoid prolonged or repeated
breathing of vapor or spray mist.
Avoid contact with eyes and skin.
Do not take internally. Close con-
tainer after using. Do not reuse
empty container. Destroy it by
perforating or crushing. Bury or
discard in a safe place. Do not con-
taminant water by cleaning of
equipment or disposal of waste.
FIRST AID: In case of skin contact,
flush with plenty of water; for eyes,
immediately flush with water for
15 minutes and get medical atten-
tion. If exposed to high concen-
tration of vapor remove to fresh
air. If swallowed CALL PHYSI-
CIAN IMMEDIATELY. DO NOT in-
duce vomiting.

**USE WITH
ADEQUATE VENTILATION**

**FOR USE BY PROFESSIONAL
APPLICATORS ONLY**

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

MD-4333 VINYL BLACK ANTI-FOULING PAINT FORMULA 129 MIL-P-159 31C TYPE II CLASS 1

KEEP OUT OF REACH OF CHILDREN

CAUTION COMBUSTIBLE

VAPOR MAY BE HARMFUL

Read Carefully CAUTIONS on Left Panel

**5 U. S. GALLONS
(18.925 LITERS)**

E.P.A. REG. NO. 39492-3

E.P.A. EST. NO.

**ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENT**

Cuprous Oxide 56.84%
INERT INGREDIENTS . . . 43.16%

100.00%

*Equivalent to 50.49%
Metallic Copper

BATCH NO.

BEST AVAILABLE COPY

Direct

Be sure the
free of me
oil. Remo
wire brush
oughly bo
pouring fr
to another
time to tin
Apply one
ship bottom
spraying,
DEVTRAN®
not add c
paint. Al
coats.

Anti-Foulin
plied over
and shoul
to metal.
anytime a
under goo

MA

AC

0

Under U.
Fungicide
as amend
registered
EPA Reg

DEVOE

Division of
Louisville, Ky.