PRECAUTIONARY STATEMENTS

DANGER

HAZARD TO HUMANS AND **DOMESTIC ANIMALS**

and the first of the contract of the second The Contract of Seaton lowed. To rit treathe vagor th schap

PRACTICAL TREATMENT

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention, If swallowed, do not induce vomiting. This product contains petroleum distilla.es. Get medical attention. If in eyes immediately flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate vater by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

CHEMICAL AND PHYSICAL HAZARDS

o not use or store near heat or open hame



PAINTS & COATINGS · WORLD-WIDE

DEVRAN® FORMULA 218 ACCEPTE PERMANENT RED ANTI-FOULING PAINT **MD-3888**

Att 5 = error man i 🦠 🔻 🗸 with the transferring EA : 3 37 49 2-35

KEEP OUT OF REACH OF CHILDREN DANGER/

SEE SIDE PANEL FOR PRECAUTIONARY STATEMENTS

E.P.A. EST. NO.

5 U. S. GALLONS (18.925 LITERS)

E.P.A. REG. NO. 39492-35

ACTIVE INGREDIENTS* Cuprous Oxide 30.25% Bis (Tributyltin) Oxide). 2.00% INERT INGRÉDIENTS 67.75%

100.00% *Equivalent to 26.8% Metallic Copper and 0.79% Metallic Tin

CONTAINS PETROLEUM DISTILLATES

BATCH NO.

Directions for Use

it is a violation of Federal Law to use this product in a mainer inconsistent with its labeling.

Devran / the fem was fine - for application to underwater

areas of steel, aluminum, fiberglass or wood vessels subject to fouling by barnacles, algae, tube worms and other fouling organisms. Surface to be coated should be clean of grease. oil, dirt and moisture. De not apply directly to metal surfaces. A suitable barrier coat should be applied to steel and aluminum surfaces; a primer is recommended for fiberglass. and wood surfaces. Apply by spray, brush or roller. For spray, airless spray is strongly recommended. When spraying, applicators must use appropriate NIOSH approved respirators. Protective clothing, rubber gloves and goggles should be worn by applicators. Contaminated clothing should be laundered before reuse. Clean up with #1 Solvent, 사회학과 Launching may be accomplished as soon as coating is dry, or later if desired.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal — Pesticide, paint or rinsate that cannot be used according to label directions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act.

Container Disposal - Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

FOR USE IN COMMERCIAL SHIPYARDS ONLY

DEVOE MARINE COATINGS CO.

Division of GROW GROUP INC.

Louisville, Ky. 40207

MADE IN U.S.A.

BEST AVAILABLE COPY