

PRECAUTIONARY STATEMENTS

DANGER

HAZARD TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes skin burns and eye irritation. Harmful if absorbed through skin or inhaled. Do not get on skin, clothing or in eyes. May be a dermal sensitizer. Wear a face shield and rubber gloves when handling. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing, and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed. Do not breathe vapor or spray mist.

PRACTICAL TREATMENT

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention. If swallowed, do not induce vomiting. This product contains petroleum distillates. Get medical attention. If in eyes, immediately flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

CHEMICAL AND PHYSICAL HAZARDS

Do not use or store near heat or open flame.

DEVOLVE

MARINE

PAINTS & COATINGS • WORLD-WIDE

ACCEPTED ABC™ ANTI-FOULING COATING
FORMULA #2 RED MD-4754

JUL 26 1982
Under the provisions of the Federal Insecticide, Fungicide, and Rodenticide Act, this product is registered under EPA Reg. No. 31492-37

**KEEP OUT OF REACH OF CHILDREN
DANGER**

SEE SIDE PANEL FOR PRECAUTIONARY STATEMENTS

**5 U. S. GALLONS
(18.925 LITERS)**

E.P.A. REG. NO. 39492-39
EPA EST. NO.

ACTIVE INGREDIENTS*
Cuprous Oxide 37.92%
Bi (Tributyltin) Oxide . . . 2.21%
INERT INGREDIENTS 59.87%

100.00%

*Equivalent to 33.6% Metallic Copper and 0.88% Metallic Tin

**CONTAINS
PETROLEUM DISTILLATES**

BATCH NO.

Directions for Use:

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

AFC. Int. Hulling Compound

— for application to underwater areas of steel, aluminum, fiberglass or wood vessels subject to fouling by barnacles, algae, tube worms and other fouling organisms. Surface to be coated should be clean of grease, oil, dirt and moisture. Do not apply directly to metal surfaces. A suitable barrier coat should be applied to steel and aluminum surfaces; a primer is recommended for fiberglass and wood surfaces. Apply by spray, brush or roller. For spray, airless spray is strongly recommended. When spraying, applicators must use appropriate NIOSH approved respirators. Protective clothing, rubber gloves and goggles should be worn by applicators. Contaminated clothing should be laundered before reuse. Clean up with *1* Solvent, *MD1134*. Launching may be accomplished as soon as coating is dry, or later if desired.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal — Pesticide, paint or rinsate that cannot be used according to label directions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act.

Container Disposal — Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

FOR USE IN COMMERCIAL SHIPYARDS ONLY

DEVOE MARINE COATINGS CO.

Division of **GROW GROUP INC.**

Louisville, Ky. 40207

MADE IN U. S. A.