

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND
DOMESTIC ANIMALS



STATEMENT OF PRACTICAL TREATMENT

In case of contact immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician.

If inhaled, remove to fresh air.

If swallowed, drink 1 or 2 glasses of water and induce vomiting by sticking finger in back of throat. Never give anything by mouth to an unconscious person.

WARNING

Harmful if swallowed. (eye and skin irritation. Do not get in eyes, on skin or on clothing. Avoid breathing vapor or spray mist. Wear goggles or face shield and rubber gloves when handling.

ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL HAZARDS


Flammable: Keep away from heat or open flame.

MOLUX A/F SUPER TROPICAL 890

ANTIFOULING COATING

ACTIVE INGREDIENT	
CUPROUS OXIDE	24.8%
INERT INGREDIENT	75.2%
TOTAL	100.0%

This product contains 3 lbs. of cuprous oxide per gallon.



KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements.

FOR INDUSTRIAL USE ONLY

BYWATER COATINGS, DIV. OF

BYWATER SALES & SERVICE CO., INC.
1610 ENGINEERS ROAD - (504) 394-5100
BELLE CHASSE, LOUISIANA 70037

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide, spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

Triple rinse containers and dispose of in an approved landfill or bury in a safe place. Consult Federal, State or local disposal authorities for approved alternative procedures.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Remove grease, dirt, oil, dust and other foreign matter by suitable cleaning methods. Apply only over recommended primer and anti-corrosives.

Agitate with power mixer until pigments are well dispersed. Thin only for workability and not more than 1 pint per gallon. Apply by spray overlapping each pass 50%. Refer to BYCO technical data for recommended film thickness and spray equipment.

NOTE: When product is used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30CFR11.

EPA ESTABLISHMENT NO. 39493-LA-01
EPA REGISTRATION NO. 39493-3
NET CONTENTS - 5 GALLONS

COMPANY NUMBER 39493-

PRODUCT SERIAL NO. 4

LABEL APPROVAL DATE 5.28.85