

EWS 515

2  
39525-4

**ACTIVE INGREDIENT**

Polyoxyethylene (dimethyliminol) ethylene  
(dimethyliminol) ethylene dichloride 15.0

**INERT INGREDIENT**

85.0

This product contains 1.29 lb. of active ingredient per gallon and weighs 8.58 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION:** Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

**FIRST AID:** If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

**DIRECTIONS FOR USE**  
**GENERAL CLASSIFICATION**

See Part 1 of Federal law to use this product in a manner consistent with its labeling.

EWS 515 is used to control bacteria in cooling towers, air wash systems, and other water cooling towers. It is not to be used in systems that are used to remove algae, growth, bacterial coating, slime, and other deposits. An initial slug addition of 4.0 to 10.0 fluid ounces of EWS 515 per 1000 gallons of water to provide a concentration of 3.2 to 8.0 parts per million of EWS 515 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.0 to 10.0 fluid ounces of EWS 515 per 1000 gallons of water (8.0 to 80 parts per million of EWS 515) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

EWS 515 is used to control bacteria in industrial air washing systems that contain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 14.8 to 24.7 fluid ounces of EWS 515 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 10.1 to 24.7 fluid ounces of EWS 515 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

**STORAGE & DISPOSAL:** Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinse that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

**METAL CONTAINERS:** Triple-rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

**PLASTIC CONTAINERS:** Do not reuse empty container. Triple-rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by  
Environmental Water Services, Inc.  
34147 Sibley Court  
Livonia, MI 48150

EPA REG. NO. 39525-4

EPA EST. NO. 39525 MI-1

**NET CONTENTS**