

muralo[®]

Semi-transparent
lumber jacket

ACCEPTED
with COMMENTS
by EPA Letter Dated:

MAR 2 1983

Oil-base
EXTERIOR/INTERIOR

Stain and Wood Preservative

1553 FRUITWOOD BROWN

One Gallon (3.785 Liters)

Active Ingredients

3-Iodo-2-Propynyl	
Butyl Carbamate	0.5%
Folpet N-(Trichloromethyl)	
Thiophthalimide	0.5%
Inert Ingredients	99.00%
Total	100.0%

EPA Reg. No. _____

EPA Est. No. _____

Keep out of reach of children

CAUTION! COMBUSTIBLE!

See Other Cautions on Back Panel.



Muralo Stain & Wood Preservative

Protects against mildew, wood rot and discoloration

Muralo Semi-Transparent Stain & Wood Preservative is especially formulated with penetrating oils, wood preservatives and a water repellent to beautify, penetrate and protect wood against rot, decay, mildew and weathering elements. It is available in clear and attractive woodtone colors that highlights and protects wood's natural beauty. Muralo Semi-Transparent Stain & Wood Preservative is recommended only for above ground use.

RECOMMENDED USES: Apply to new or old bare or previously stained wood surfaces, inside or outside, including decks, fences, shakes and shingles (including cedar), wood siding, picnic tables, furniture, and interior and exterior trim.

May be applied over coats of other similar stains. It should not be applied over stain finishes with high contents of water repellents unless sufficient weathering (usually 1 to 2 years) had occurred to allow for penetration.

Precautionary Statements: Hazards to Humans and Domestic Animals

WARNING! HARMFUL OR FATAL IF SWALLOWED.

If swallowed do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

Avoid breathing vapor or spray mist, which may be toxic if breathed excessively. Use in well ventilated area. Avoid contact with skin, eyes or clothing. In case of contact, immediately remove contaminated clothing and wash skin with soap and water; for eyes flush with plenty of water and get medical attention. Wash clothing before reusing.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of water. Apply this product only as specified on this label.

PHYSICAL or CHEMICAL HAZARDS: COMBUSTIBLE!

KEEP AWAY FROM HEAT AND OPEN FLAME.

Keep container closed when not in use. Soak contaminated clothes in water after use to avoid spontaneous combustion.

SURFACE PREPARATION: The surface to be coated must be clean, firm, completely dry, and free from all dirt, dust, grease, oil wax, and mildew. Muralo Stain and Wood Preservative will resist mildew attack after application; however, it will not kill mildew present prior to staining. Test for mildew by applying a 50/50 solution of bleach and water. Mildew is present if application area lightens. Scrub all mildew infected surfaces with a solution of:

1 Qt. Household bleach to 3 qts. warm water. Let stand 30 minutes, then rinse with clear water. Apply Muralo Stain & Wood Preservative only after area is completely dry.

DIRECTIONS FOR USE:

GENERAL CLASSIFICATION: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Before use, Thoroughly Mix Contents of can. Stir occasionally during use to keep color uniform. Use on clean, dry, unprimed wood or previously semi-transparent stained surfaces which are free of all mildew.

Apply liberally by brush, roller, spray or by dipping (siding 3 minutes, millwork 5 minutes). If stain is not freely absorbed by wood, allow surface to weather until adequate absorption is attained. Color will vary somewhat on different woods from color card; re-coating over other colors may also affect the color. A sample brush out is recommended. Do not use on abraded plywood. The more preservative absorbed by the wood, the longer and more effective the protection. Thoroughly cover cut ends and joints. For best results, apply in the shade at 40° to 90°F. Do not thin. Muralo Stain and Wood Preservative dries to the touch rapidly, but thorough drying requires 24 hours. If desired, a second coat may be applied at any time after the initial application. Clean Muralo Stain and Wood Preservative from brushes, etc. with mineral spirits or turpentine. **Coverage:** Approximately 400 sq. ft. per gallon when brushed on smooth woods. Textured surfaces absorb more stain.

STORAGE AND DISPOSAL:

Storage: Do not use or store near heat or open flame. Avoid storage near feed or food products.

Disposal: Do not reuse empty container. Wrap and put in trash collection.

The Muralo Company, Inc. Bayonne, New Jersey 07002 U.S.A.

Chicago/Los Angeles/Atlanta

Made in U.S.A.

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460	EPA REGISTRATION NO.	DATE OF ISSUANCE MAR 2 1983
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT	

NOTICE OF PESTICIDE: REGISTRATION
 REREГИSTRATION
(Under the Federal Insecticide, Fungicide and Rodenticide Act, as amended)

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

160	27129
18	1

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------