

KEYSTONE MB-250

ACTIVE INGREDIENT:

2-Hydroxypropyl methanethiolsulfonate25%

INERT INGREDIENT75%

Total 100%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

STATEMENT OF PRACTICAL TREATMENT

If product gets in eyes, flush with plenty of water for at least 15 minutes. Call a physician. In case of skin contact, wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage. Be alert for signs of circulatory shock, respiratory depression, and convulsion may occur.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye damage. Causes severe skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling this product. Remove and wash contaminated clothing. Do not take internally.

ENVIRONMENTAL HAZARDS: Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your Regional office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Keystone MB-250 is used to control the growth of bacteria in commercial and industrial recirculating cooling water systems, and industrial nonpotable water supply systems. It should not be used in water intended for drinking or food preparation. Before treatment with Keystone MB-250 is begun, cooling water systems should be cleaned thoroughly to remove slime and other deposits. Then they should be drained, refilled with water, and treated with an initial slug dose of 1.0 to 4.0 fluid ounces of Keystone MB-250 per 1000 gallons of water in the system. Repeat until control is evident. Then treat with 0.2 to 4.0 fluid ounces per 1000 gallons of water every 1 to 5 days, or as needed. To control the growth of bacteria in industrial water supply systems, treat with 0.2 to 2.0 fluid ounces of Keystone MB-250 per 1000 gallons of water entering the system, continuously or as needed.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drum should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

EPA REG. NO. 39743-13

EPA EST. NO. 39743-AL-1

NET CONTENTS
ACCEPTED

MAR 11 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under
EPA Reg. No. 39743-13



Manufactured By:

KEYSTONE LABORATORIES, INC.

(205) 385-4783

Decatur, Alabama