

# WPC Alga-Trol 60

ACCEPTED  
39920-3  
JULY 29 1981  
U.S. Environmental Protection Agency  
Wichita Falls, Texas 76710

## ACTIVE INGREDIENT:

Poly(oxyethylene (dimethyliminio) ethylene  
(dimethyliminio) ethylene dichloride) 60.0%

INERT INGREDIENT 40.0%

This product contains 5.76 lb. of active ingredient per gallon and weighs 9.6 lb per gallon.

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**CAUTION:** Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

**FIRST AID:** If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

## DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

WPC Alga-Trol 60 is used to control the growth of algae in swimming pools, exterior spas, whirlpools, and hot tubs. For maximum effectiveness pools, spas, whirlpools, and hot tubs containing heavy growth of algae should be cleaned prior to using WPC Alga-Trol 60.

For pools having just visible algae growth add an initial dose of 11 to 17 fluid ounces of WPC Alga-Trol 60 per 10,000 gallons of water and remove settled algae debris by cleaning. For treatment of a freshly cleaned and filled pool add initially 6 to 11 fluid ounces of WPC Alga-Trol 60 per 10,000 gallons of water. Subsequent additions of 2 to 4 fluid ounces of WPC Alga-Trol 60 per 10,000 gallons of water should be made every 5 to 7 days after initial treatment for maintenance.

Spas, whirlpools, or hot tubs having just visible algae growth require an initial dose of 1 to 2 fluid ounces of WPC Alga-Trol 60 per 1000 gallons of water. For treatment of a freshly cleaned and filled spa, whirlpool, or hot tub, add initially 0.6 to 1.1 fluid ounces of WPC Alga-Trol 60 per 1,000 gallons of water. Subsequent additions of 0.2 to 0.4 fluid ounces of WPC Alga-Trol 60 should be made every 5 to 7 days after initial treatment for maintenance.

WPC Alga-Trol 60 is compatible with those chemicals normally used to treat pools and spas and is effective at both acid and alkaline pH. WPC Alga-Trol 60 can be used in pools and spas treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix WPC Alga-Trol 60 with concentrated dry or liquid chlorine products.

**STORAGE & DISPOSAL:** Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

**METAL CONTAINERS:** Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

**PLASTIC CONTAINERS:** Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by  
Westmoreland Pool Company  
4613 Wyoming  
Wichita Falls, TX 76710

EPA REG. NO. 39920-3

EPA EST. NO.

NET CONTENTS

17